



Revision 20181012

# SABIC<sup>®</sup> PP 511MNK40T

# POLYPROPYLENE IMPACT COPOLYMER REGION ASIA

#### **DESCRIPTION**

SABIC<sup>®</sup> PP 511MNK40T is a high fluidity polypropylene impact copolymer with high stiffness and medium impact strength. It contains nucleating & antistatic agents.

### TYPICAL APPLICATIONS

SABIC® PP 511MNK40T can be used for housewares and thin-walled injection articles.

# TYPICAL PROPERTY VALUES

PROPERTIES TYPICAL VALUES UNITS **TEST METHODS** POLYMER PROPERTIES Melt Flow Rate at 230°C and 2.16 kg 29 g/10 min ISO 1133 905 ISO 1183 Density kg/m<sup>3</sup> MECHANICAL PROPERTIES (1) Tensile Strength at Yield 25 MPa ISO 527-2 Flexural Modulus (1% Secant) 1350 MPa ISO 178 Charpy Impact Strength Notched at 23 °C 9 kJ/m² ISO 179-1 at -20 °C 5 kJ/m² ISO 179-1 Rockwell Hardness R-scale 95 ISO 2039-2 THERMAL PROPERTIES Heat deflection temperature °C at 455kPa 100 ISO 75-2

(1) Based on injection molded specimens.

### HEALTH, SAFETY AND FOOD CONTACT REGULATIONS

SABIC® PP 511MNK40T is suitable for food contact application. Detailed information is provided in relevant documents / certificates and for additional specific information please contact SABIC local representative.

#### STORAGE AND HANDLING

Polypropylene resin should be stored in a manner to prevent a direct exposure to sunlight and/or heat. The storage area should also be dry and preferably do not exceed 50°C. SABIC would not give warranty to bad storage conditions which may lead to quality deterioration such as color change, bad smell and inadequate product performance. It is advisable to process PP resin within 6 months after delivery.





# DISCLAIMER

Any sale by SABIC, its subsidiaries and affiliates (each a "seller"), is made exclusively under seller's standard conditions of sale (available upon request) unless agreed otherwise in writing and signed on behalf of the seller. While the information contained herein is given in good faith, SELLER MAKES NO WARRANTY, EXPRESS OR IMPLIED, INCLUDING MERCHANTABILITY AND NONINFRINGEMENT OF INTELLECTUAL PROPERTY, NOR ASSUMES ANY LIABILITY, DIRECT OR INDIRECT, WITH RESPECT TO THE PERFORMANCE, SUITABILITY OR FITNESS FOR INTENDED USE OR PURPOSE OF THESE PRODUCTS IN ANY APPLICATION. Each customer must determine the suitability of seller materials for the customer's particular use through appropriate testing and analysis. No statement by seller concerning a possible use of any product, service or design is intended, or should be construed, to grant any license under any patent or other intellectual property right.