

**g**  
**CYCOLOY**  
**MC8100-100**

Print Date: 09-26-2002

Page 1 of 7

**GE Plastics**

Revision Date: 09/26/02

## Material Safety Data Sheet

**SECTION 1: PRODUCT AND COMPANY IDENTIFICATION**General Electric Co.  
One Plastics Ave.  
Pittsfield, MA 01201GE Plastics Canada, Ltd.  
2300 Meadowvale Blvd.  
Mississauga, ONT L5N 5P2**PHONE NUMBERS**Emergency Medical (24 HOUR)  
Emergency Transportation/CHEMTREC (24 HOUR)  
Other Emergency Information (24 HOUR)

Non-Emergency Information :

For Resin Products  
For Structured Products**PRODUCT IDENTIFICATION**

**PRODUCT IDENTIFIER:** CYCOLOY  
MC8100-100  
Poly (bisphenol-A-carbonate) [CASRN 111211-39-3]/Poly (acrylonitrile-butadiene-styrene) [CASRN 9003-56-9] blend

**PRODUCT DESCRIPTION:** Synthetic thermoplastic polymer.

**PRODUCT USE:** May be used to produce molded or extruded articles or as a component of other industrial products.

**SECTION 2: COMPOSITION/INFORMATION ON INGREDIENTS**

Components listed below are physical or health hazards as defined in the Hazard Communication Standard. The quantities represent typical or average values for the materials shown. Additional compositional data are provided in Section 15, REGULATORY INFORMATION, subject to supplier notification requirements.

<u>Component Name</u>	<u>%</u>	<u>CAS Number</u>	<u>OSHA PEL</u>	<u>ACGIH TWA</u>	<u>GE Recommended Exp. Limits</u>
This product does not contain any reportable hazardous materials.					

**g****CYCOLOY****MC8100-100**

Print Date: 09-26-2002

Page 2 of 7

**GE Plastics**

Revision Date: 09/26/02

**SECTION 3: HAZARDS IDENTIFICATION****EMERGENCY OVERVIEW:**

- Pellets with slight or no odor.
- Spilled material may create slipping hazard.
- Can burn in a fire creating dense toxic smoke.
- Molten plastic can cause severe thermal burns.
- Fumes produced during melt processing may cause eye, skin, and respiratory tract irritation. Severe over-exposure may result in nausea, headache, chills, and fever.
- Secondary operations, such as grinding, sanding, or sawing can produce dust which may present an explosion or respiratory hazard.

HMIS Ratings: Health = 0; Flammability = 1; Reactivity = 0; PPE = B

**POTENTIAL HEALTH EFFECTS**

INGESTION: No hazard in normal industrial use.  
SKIN ABSORPTION: No absorption hazard in normal industrial use.  
EYE CONTACT: Can cause mechanical irritation if dusts are generated.  
SKIN CONTACT: Unlikely to cause irritation even on repeated contact.

**CHRONIC / CARCINOGENICITY**

NTP: Not Tested.  
OSHA: Not Regulated.  
IARC: Not Listed.

NOTE: OSHA, IARC and/or NTP have listed carbon black and heavy metals, present in some colorants, as carcinogens. If these colorants are present in this product, they are shown in SECTION 2. These colorants are essentially bound to the plastic matrix and are unlikely to contribute to workplace exposure under recommended processing conditions.

Processing fumes may cause irritation to the eyes, skin, and respiratory tract. In cases of severe exposure, nausea and headache can also occur.

Grease-like processing fume condensates on ventilation ductwork, molds, and other surfaces can cause irritation and injury to skin.

MEDICAL RESTRICTIONS: There are no known human health effects aggravated by exposure to this product. However, certain sensitive individuals and individuals with respiratory impairments may be affected by exposure to components in the processing vapors.

**SECTION 4: FIRST AID MEASURES**

**g**  
**CYCOLOY**  
**MC8100-100**

Print Date: 09-26-2002

Page 3 of 7

**GE Plastics**

Revision Date: 09/26/02

**EYES:** Immediately flush eyes with plenty of water. Get medical attention if irritation develops or persists. After initial flushing, remove any contact lenses.

**SKIN:** Wash with soap and water. Get medical attention if irritation develops or persists. For hot product, immediately immerse in or flush affected area with large amounts of cold water to dissipate heat. Cover with clean cotton sheeting or gauze and get prompt medical attention.

**INGESTION:** No hazard in normal industrial use. Do not induce vomiting. Seek medical attention if symptoms develop.

**INHALATION:** No specific treatment is necessary since this material is not likely to be hazardous by inhalation.

**PROCESSING FUMES:** Processing fumes inhalation may be irritating to the respiratory tract. If symptoms are experienced remove victim from the source of contamination or move victim to fresh air and obtain medical advice.

**SECTION 5: FIRE FIGHTING MEASURES**

**FIRE FIGHTING:** Do not enter fire area without proper protection including self-contained breathing apparatus and full protective equipment. Fight fire from a safe distance and a protected location due to the potential of hazardous vapors and decomposition products.

**EXTINGUISHING MEDIA:** Water spray and foam. Carbon dioxide and dry chemical are not recommended because their lack of cooling capacity may permit re-ignition.

**CONDITIONS OF FLAMMABILITY:** Requires a continuous flame source to ignite.

**AUTOIGNITION TEMPERATURE:** 630 C (1166 F), estimated 541 C (1006 F) estimated

**EXPLOSION DATA:** Material not sensitive to mechanical impact but is sensitive to static discharge under dust cloud conditions.

**HAZARDOUS COMBUSTION PRODUCTS:** Intense heat, smoke, carbon dioxide, carbon monoxide, hydrocarbon fragments Hydrogen cyanide

**SECTION 6: ACCIDENTAL RELEASE MEASURES**

**GENERAL:** Gather and store in a closed container pending a waste disposal evaluation. Allow molten material to solidify before disposal.

**SECTION 7: HANDLING AND STORAGE**

**HANDLING:** Follow recommendations on label and in processing guide. Prevent contact with skin and eyes. Use good industrial hygiene practices. Provide adequate ventilation. Secondary operations such as grinding, sanding, or sawing may produce a dust explosion hazard. Use aggressive housekeeping activities to prevent dust accumulation: employ bonding, grounding, venting, and explosion relief provisions in accordance with accepted engineering practices.

**STORAGE:** Store in a cool dry place. Avoid excessive heat and ignition sources.

**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

**g**  
**CYCOLOY**  
**MC8100-100**

Print Date: 09-26-2002

Page 4 of 7

**GE Plastics**

Revision Date: 09/26/02

**ENGINEERING CONTROLS:**

A continuous supply of fresh air to the workplace together with removal of processing fumes through exhaust systems is recommended. Processing fume condensate may be a fire hazard and toxic; remove periodically from exhaust hoods, ductwork, and other surfaces using appropriate personal protection. Local ventilation requirements must be determined to limit exposure to processing fumes in the workplace.

**PERSONAL PROTECTION****EYE/FACE:**

Wear safety glasses with side shields or chemical goggles. In addition, use full-face shield when cleaning processing fume condensates from hoods, ducts, and other surfaces.

**SKIN:**

When handling pellets or powder, avoid prolonged or repeated contact with skin. Wear long pants, long sleeves, well insulated gloves, and a face shield during melt processing. Appropriate clothing - including chemical resistant gloves - should be worn to prevent contact with processing fumes condensate.

**RESPIRATORY:**

When using this product at elevated temperatures, implement engineering systems, administrative controls, or a respiratory protection program (including a respirator approved for protection from organic vapors, acid gases, and particulate matter) if processing fumes are not adequately controlled or operators experience symptoms of overexposure. If dust or powder are produced from secondary operations such as sawing or grinding, use a respirator approved for protection from dust.

**SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES****PHYSICAL STATE:**

Solid

**COLOR:**

Plastic pellet with slight odor.

**MELTING POINT:**

This product does not exhibit a sharp melting point but softens gradually over a wide range of temperatures.

**VAPOR PRESSURE (mmHg):**

Negligible.

**SPECIFIC GRAVITY (WATER = 1):**

&gt;1

**WATER SOLUBILITY:**

Insoluble

**% VOLATILES:**

Negligible

**EVAPORATION RATE:**

Negligible.

**OCTANOL/WATER PARTITION**

Not established

**COEFFICIENT:****SECTION 10: STABILITY AND REACTIVITY****STABILITY:**

Stable

**REACTIVITY:**

Not reactive under recommended conditions of handling, storage, processing, and use.



**g**  
**CYCOLOY**  
**MC8100-100**

Print Date: 09-26-2002

Page 5 of 7

**GE Plastics**

Revision Date: 09/26/02

**CONDITIONS TO AVOID:**

Do not exceed melt temperature recommendations in product literature. In order to avoid autoignition/hazardous decomposition of hot thick masses of plastic, purgings should be collected in small, flat, shapes or thin strands to allow for rapid cooling. Quench in water. Do not allow product to remain in barrel at elevated temperatures for extended periods of time: purge with a general purpose resin. (See Section 8 for respiratory protection advice.)

**HAZARDOUS DECOMPOSITION PRODUCTS**

Processing fumes evolved at recommended processing conditions may include trace levels of the following materials: phenols, alkylphenols, diarylcarbonate, styrene, acrylonitrile, acrolein, acetaldehyde, acetophenone, ethylbenzene, cumene, 4-vinylcyclohexene

**SECTION 11: TOXICOLOGICAL INFORMATION****ACUTE HEALTH HAZARDS****ACUTE ORAL:**  
**EYE CONTACT:**

Oral LD50 Rat >5 g/kg Oral toxicity is estimated from tests on similar materials. Product not considered primary eye irritant. When similar products, in finely divided form, were placed into the eyes of rabbits, slight transient redness or discharge occurred. This is consistent with the expected slightly abrasive nature of the resin particles.

**SKIN CONTACT:**

Product not considered primary skin irritant. Draize Skin Primary Irritation Score (rabbit) for similar products, in finely divided form, for a 24-hour exposure is 0. Not expected to be a skin sensitizer based on results of Modified Buehler Guinea Pig Sensitization Test from similar products. Dermal LD50 (rabbit) > 2g/kg, estimated.

**SUBCHRONIC HEALTH HAZARDS**

**SUBCHRONIC TOXICITY:** No data available.

**CHRONIC HEALTH HAZARDS****CARCINOGENIC PROPERTIES**

**NTP:** Not Tested.  
**OSHA:** Not Regulated.  
**IARC:** Not Listed.

**SECTION 12: ECOLOGICAL INFORMATION****GENERAL:**

This material is not expected to be harmful to the ecology.

**SECTION 13: DISPOSAL INFORMATION****WASTE DISPOSAL:**

Recycling is encouraged. Landfill or incinerate in accordance with federal, state and local requirements. Collected processing fume condensates and incinerator ash should be tested to determine waste classification.

**POSSIBLE EPA WASTE CODES:** No data.



**g**  
**CYCOLOY**  
**MC8100-100**

Print Date: 09-26-2002

Page 6 of 7

**GE Plastics**

Revision Date: 09/26/02

**SECTION 14: TRANSPORTATION INFORMATION**

REGULATORY STATUS: Not Regulated.

**SECTION 15: REGULATORY INFORMATION****TOXIC SUBSTANCES CONTROL ACT (TSCA):** This product is in compliance with all rules and orders of TSCA.**WHMIS PRODUCT CLASSIFICATION:** D2

If any components in this product are SARA 313 listed as reportable, they are shown below. The quantities listed for elements represent typical or average values for compounds containing the element.

Component	CAS Number	%
No SARA 313-listed chemicals in this product.		

If any components in this product are known to the State of California to cause cancer and/or are reproductive hazards, they are listed below:

Component	Reason Listed	CAS Number	%
Not Applicable			

**SECTION 16: OTHER INFORMATION**

Prepared by: Product Stewardship

® AVP, COLORXPRESS, CYCOLAC, CYCOLOY, CYTRA, ENDURAN, GELON, GELOY, GEMAX, GTX, LEXAN, LEXGUARD, LOMOD, MAGIX, NORLYL, NORLYL GTX, NORLYL PPX, POLYMERLAND, PPO, PPX, PREVEX, SOLLX, SUPEC, ULTEM, VALOX, VISUALFX, XENOY and XYLEX are registered or pending trademarks of the General Electric Co.

**DISCLAIMER:** This Material Safety Data Sheet [MSDS] information is provided based on the Hazard Communication Regulations for your region or country and for the use of the persons required to receive this information under those regulations. The information is neither designed nor recommended for any other use or for use by any other person, including for compliance with other laws. GE does not warrant the suitability for use of this MSDS for any other material or product not specifically identified herein. GE does not warrant the accuracy or authenticity of this MSDS unless it has been obtained directly from GE, or posted or viewed on a GE website. Modification of this MSDS, unless specifically authorized by GE, is strictly prohibited. This MSDS is based on information, that is believed to be reliable, but may be subject to change as new information becomes available. Because it is not possible to anticipate all conditions of use, additional safety precautions may be required. Since the use of this material is not under General Electric Company's control, each user is responsible for making its own determination as to the safe and proper handling of this material in its own particular use of this material. GENERAL ELECTRIC COMPANY MAKES NO REPRESENTATION OR WARRANTY, EITHER EXPRESS OR IMPLIED, INCLUDING AS TO MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.



**g**  
**CYCOLOY**  
**MC8100-100**

Print Date: 09-26-2002

Page 7 of 7

**GE Plastics**

Revision Date: 09/26/02

Each user should read and understand this information and incorporate it into individual site safety programs as required by applicable hazard communication standards and regulations.

ABBREVIATIONS:   ACGIH: American Conference of Governmental Industrial Hygienists  
                          CAS: Chemical Abstracts Service  
                          CFR: Code of Federal Regulations  
                          CPR: Cardiopulmonary Resuscitation  
                          EPA: Environmental Protection Agency  
                          HMIS: Hazardous Material Identification System (National Paint and Coatings Association)  
                          IARC: International Agency for Research on Cancer  
                          OSHA: Occupational Health and Safety Administration (U.S.)  
                          NTP: National Toxicology Program  
                          PEL: Permissible Exposure Limit  
                          PPE: Personal Protective Equipment  
                          SARA 313: Superfund Amendments and Reauthorization Act, Section 313  
                          TLV: Threshold Limit Value  
                          TSCA: Toxic Substance Control Act  
                          WHMIS: Workplace Hazardous Materials Information System (Canada)

