



组件 - 塑料
UL 档案号: E207780

SABIC JAPAN L L C
PACIFIC GRADES - RESIN, 2-2 KINUGAOKA, MOKA-SHI TOCHIGI-KEN 321-4392 JP



Geloy: XTPMFR10

PC/Siloxane/ASA, pellets

NOTE - Material designation may be followed by a color nomenclature consisting of either an alpha/numeric or numeric/alpha combination.

可燃性	值	测试方法
UL 阻燃等级		UL 94
0.8 mm, ALL	V-1	IEC 60695-11-10, -20
1.0 mm, ALL	V-0	
1.5 mm, ALL	V-0	
2.0 mm, ALL	V-0, 5VB	
3.0 mm, ALL	V-0, 5VB	
灼热丝易燃指数		IEC 60695-2-12
0.8 mm	960 °C	
1.0 mm	960 °C	
2.0 mm	960 °C	
3.0 mm	960 °C	
热灯丝点火温度		IEC 60695-2-13
0.8 mm	875 °C	
1.0 mm	825 °C	
2.0 mm	775 °C	
3.0 mm	775 °C	
电气性能	值	测试方法
热丝引燃 (HWI)		UL 746
0.8 mm	PLC 3	
1.0 mm	PLC 0	
1.5 mm	PLC 0	
2.0 mm	PLC 0	
3.0 mm	PLC 0	
高电弧燃烧指数(HAI)		UL 746
0.8 mm	PLC 0	
1.0 mm	PLC 0	
1.5 mm	PLC 0	
2.0 mm	PLC 0	
3.0 mm	PLC 0	
热性能	值	测试方法
RTI Elec		UL 746
0.8 mm	90.0 °C	
1.0 mm	90.0 °C	
1.5 mm	90.0 °C	
2.0 mm	90.0 °C	
3.0 mm	90.0 °C	



组件 - 塑料
UL 档案号: E207780



热性能	值	测试方法
RTI Imp		UL 746
0.8 mm	90.0 °C	
1.0 mm	90.0 °C	
1.5 mm	90.0 °C	
2.0 mm	90.0 °C	
3.0 mm	90.0 °C	
RTI		UL 746
0.8 mm	90.0 °C	
1.0 mm	90.0 °C	
1.5 mm	90.0 °C	
2.0 mm	90.0 °C	
3.0 mm	90.0 °C	

