

Braskem PP C7069-100NA

抗冲击共聚聚丙烯

Braskem Europe GmbH

Technical Data

产品说明			
BRASKEM C7069-100NA Polypropylene Resin has been developed for high speed injection molding in various applications. BRASKEM C7069-100NA Polypropylene Resin is a nucleated impact copolymer combining very high flow with an excellent balance of mechanical properties and organoleptic properties. It has been designed for short cycle times and excellent antistatic performance.			
Applications:			
- Thin wall packaging (margarine tubs, dairy product pots, ice cream containers/lids) - Thin wall consumer goods e.g. Flower pots, Houseware, food boxes - Caps & closures			
Process:			
High speed injection molding			
总览			
添加剂	成核剂		
特性	- 成核的 - 抗冲击共聚物 - 抗静电性 - 快的成型周期 - 良好的感官特征 - 流动性高		
用途	- 包装 - 薄壁包装 - 薄壁部件 - 护罩 - 家用货品 - 外壳		
机构评级	- FDA FCN 843 - 欧洲 No 10/2011		
加工方法	注射成型		
物理性能		额定值 单位制	测试方法
密度 / 比重		0.900 g/cm³	ASTM D792
熔流率 (熔体流动速率) (230°C/2.16 kg)		100 g/10 min	ASTM D1238
机械性能		额定值 单位制	测试方法
弯曲模量 (注塑)		1580 MPa	ISO 178
冲击性能		额定值 单位制	测试方法
简支梁缺口冲击强度 (23°C, 注塑)		4.0 kJ/m²	ISO 179/1eA
热性能		额定值 单位制	测试方法
热变形温度 (0.45 MPa, 未退火)		105 °C	ISO 75-2/B
维卡软化温度		152 °C	ISO 306/A

备注

¹ 通过这些链接您能够访问供应商资料。我们尽量保证及时更新资料；不过您可以从供应商处了解最新资料。

² 一般属性：这些不能被视为规格。

