



# Braskem PP FT120W2

Braskem America Inc. - Polypropylene Homopolymer

Wednesday, October 9, 2019

## General Information

### Product Description

Antistatic, good mold release

Applications

Suggested uses include closures, housewares

### General

Material Status	• Commercial: Active		
Availability	• North America		
Additive	• Antistatic		
Features	• Antistatic	• Good Mold Release	
Uses	• Closures	• Household Goods	
Agency Ratings	• FDA 21 CFR 177.1520		

## ASTM & ISO Properties <sup>1</sup>

Physical	Nominal Value	Unit	Test Method
Melt Mass-Flow Rate (MFR) (230°C/2.16 kg)	12	g/10 min	ASTM D1238
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength <sup>2</sup> (Yield)	37.2	MPa	ASTM D638
Tensile Elongation <sup>2</sup> (Yield)	9.0	%	ASTM D638
Flexural Modulus - 1% Secant <sup>3</sup>	1590	MPa	ASTM D790A
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact (23°C)	32	J/m	ASTM D256A
Hardness	Nominal Value	Unit	Test Method
Rockwell Hardness (R-Scale)	106		ASTM D785

### Notes

<sup>1</sup> Typical properties: these are not to be construed as specifications.

<sup>2</sup> 51 mm/min

<sup>3</sup> 1.3 mm/min



UL and the UL logo are trademarks of UL LLC © 2019. All Rights Reserved.

The information presented here was acquired by UL from the producer of the product or material or original information provider. However, UL assumes no responsibility or liability for the accuracy of the information contained on this website and strongly encourages that upon final product or material selection information is validated with the manufacturer. This website provides links to other websites owned by third parties. The content of such third party sites is not under our control, and we cannot and will not take responsibility for the information or content.

