

Braskem PP H521

聚丙烯均聚物

Braskem America Inc.

Technical Data

产品说明		
特性	水携带性低	通用
用途	- 带子 - 高速切膜纤维 - 家用货品	- 容器 - 切膜纤维 - 通用 - 外壳
机构评级	FDA 21 CFR 177. 1520	
加工方法	注射成型	

物理性能	额定值单位制	测试方法
熔流率（熔体流动速率）（230° C/2. 16 kg）	3. 6 g/10 min	ASTMD1238
机械性能	额定值单位制	测试方法
抗张强度 ³ （屈服）	37. 2MPa	ASTM D638
伸长率 ³ （屈服）	10%	纤维 ASTM D638
弯曲模量 - 1% 正割 ⁴	1650MPa	ASTM D790A
冲击性能	额定值单位制	测试方法
悬壁梁缺口冲击强度（23° C）	37 J/m	ASTM D256A
硬度	额定值单位制	测试方法
洛氏硬度（R 级）	103	ASTM D785
补充信息	额定值单位制	测试方法
Elongation of Fibers ⁵	36%	ASTMD2256
Tenacity of Fibers ⁵	4. 50 g/denier	ASTMD2256



Braskem PP H521

聚丙烯均聚物

Braskem America Inc.

购买地点

供应商

HONRUN INTERNATIONAL CO; LIMITED (鸿润创业国际有限公司)

Address: UNIT 04, BRIGHT WAY TOWER, NO. 33 MONG KOK ROAD, KOWLOON, HK.

TEL: +852-69575415

MAIL: hongrunplas@139.com

Shanghai Ponci Trading Co., Ltd (上海浜禧贸易有限公司)

Address: Room 908, JiaZheng International Building, No.28, Moyu Road, Anting Town, Jiading District, Shanghai 201805, P.R.C

TEL: +86-21-59531779 FAX: +86-21-59531775

MOB: +86-18816996168

Mail: ponci@vip.126.com QQ: 1404829350

分销商

Dong Yuming Plastics Co;Ltd (东莞市煜铭塑料科技有限公司)

Address: Guangdong Dongguan Zhangmutou Town Plastic Raw material market phase four, a building 15th

TEL: +86-769-82863948

MOB: +86-13922531319

Mail: daishulong@126.com

