

SABIC® HDPE B5206

HIGH DENSITY POLYETHYLENE

DESCRIPTION

HDPE B5206 is high density polyethylene specially developed for large blow molding / Jerry cans. The material offers high stiffness, good processability and excellent combination of stiffness/ESCR.

TYPICAL APPLICATIONS

B5206 is specially designed for Standard jerry cans, UN approved jerry cans and standard drums up to 60L The grade is intended for food contact application.

TYPICAL PROPERTY VALUES

PROPERTIES	TYPICAL VALUES	UNITS	TEST METHODS
POLYMER PROPERTIES			
Melt Flow Rate (MFR) @ 190°C & 21.6 kg load ⁽¹⁾	6.5	g/10 min	ISO 1133
Density at 23°C	952	kg/m ³	ASTM D1505
MECHANICAL PROPERTIES			
Tensile modulus ⁽²⁾	1050	MPa	ASTM D638
Tensile Strength at Yield	26	MPa	ASTM D638
Tensile Strain at Yield	10	%	ISO 527-1/-2
Charpy Notched Impact Strength (-30°C, Type 1, Notch A)	36	kJ/m ²	ISO 179
FNCT (3.5 MPa, 2 % Igepal BC/9, 80°C)	50	Hrs	ISO 16770