

POLYMERS

SABIC® HDPE PIPE P6006

PRODUCT DESCRIPTION

P6006 is black compound high density (class MRS 10 - PE 100) Polyethylene with bimodal distribution of molecular mass. It is specifically designed for pressure Pipe applications. It provides excellent stress crack resistance properties (ESCR) combined with very good long term hydrostatic strength.

TYPICAL APPLICATIONS

P6006 Pressure pipes for drinking water, irrigation, gas distribution and waste water pipes. It is also recommended for manufacture of chemical liners and containers.

TYPICAL DATA

PROPERTIES	Unit	Value ⁽¹⁾	Test Method
Melt Flow Rate			
@ 190°C & 5 kg load	g/10 min	0.23	ISO 1133
@ 190°C & 21.6 kg load		6.2	
Carbon Black content	%	2.25	ISO 6964
Density @ 23°C	Kg/m ³	959	ISO 1183
MECHANICAL PROPERTIES(2)			
Tensile Strength @ Yield ⁽³⁾	MPa	23	ISO 527-2
Tensile Elongation @ Yield ⁽³⁾	%	9	
Tensile Modulus ⁽³⁾	MPa	900	
Charpy Impact Notched			
@ 23°C	kJ/m ²	26	ISO 179
@ -30°C		13	
Hardness (Shore D)	-	63	ISO 868
THERMAL PROPERTIES			
Vicat Softening Point @ 50N (VST/B)	°C	74	ISO 306
OIT (210°C)	Min	> 20	EN 728