

SABIC® LDPE 2402H0

LOW DENSITY POLYETHYLENE

DESCRIPTION

SABIC® LDPE 2402H0 is a blown film grade which has a very broad processing window and an excellent draw down ability. The films are characterized by very good mechanical and optical properties. The grade contains no additives.

Application

SABIC® LDPE 2402H0 is typically used for thin film applications where enhanced stiffness is required, such as thin shrink films, food packaging films, bags and pouches.

Film properties

Film properties have been measured at film of 25 µm with a BUR of 3.

The film has been produced on Kiefel IBC blown film line with 200 kg/h. Die size 200 mm, die gap 0.8 mm.

This product is not intended for and must not be used in any pharmaceutical/medical applications.

TYPICAL PROPERTY VALUES

PROPERTIES	TYPICAL VALUES	UNITS	TEST METHODS
POLYMER PROPERTIES			
Melt Flow Rate (MFR)			
at 190 °C and 2.16 kg	2	dg/min	ISO 1133
Density	924	kg/m ³	ISO 1183
OPTICAL PROPERTIES			
Gloss (45°)	60	%	ASTM D2457
Haze	7	%	ASTM D1003
FILM PROPERTIES			
Impact strength	20	kJ/m	ASTM D4272
Tear strength TD	35	kN/m	ISO 6383-2
Tear strength MD	80	kN/m	ISO 6383-2
Tensile test film			
Stress at break TD	20	MPa	ISO 527-3
Stress at break MD	30	MPa	ISO 527-3
Yield stress TD	12	MPa	ISO 527-3
Modulus of elasticity TD	240	MPa	ISO 527-3
Tensile test film			
Strain at break MD	>200	%	ISO 527-3
Strain at break TD	>500	%	ISO 527-3
Coefficient of friction	1.0	-	ASTM D1894
Blocking	20	g	SABIC method
Re-blocking	<5	g	SABIC method
THERMAL PROPERTIES			
Vicat Softening Temperature			
at 10 N (VST/A)	96	°C	ISO 306