

SABIC® LDPE HP2027LN

LOW DENSITY POLYETHYLENE

DESCRIPTION

HP2027LN is a Low Density Polyethylene grade with increase density. It typically exhibits better draw down ability with high output. Films typically have excellent optics and high rigidity. It contains slip and antiblock additives.

TYPICAL APPLICATIONS

Thin shrink film, lamination film, packaging film for food and industrial goods, bags & pouches. These grades are typically suitable where high optics, enhance stiffness and down gauging, are required.

TYPICAL PROPERTY VALUES

PROPERTIES	TYPICAL VALUES	UNITS	TEST METHODS
POLYMER PROPERTIES			
Melt Flow Rate (MFR)			
at 190°C and 2.16 kg	2.0	g/10 min	ASTM D1238
FORMULATION			
Slip agent	<input checked="" type="checkbox"/>	-	-
MECHANICAL PROPERTIES			
Dart Impact Strength	2	g/μm	ASTM D1709
OPTICAL PROPERTIES			
Haze ⁽¹⁾	4	%	ASTM D1003
FILM PROPERTIES			
Tensile Properties			
stress at break, MD	27	MPa	ASTM D882
stress at break, TD	18	MPa	ASTM D882
strain at break, MD	326	%	ASTM D882
strain at break, TD	522	%	ASTM D882
stress at yield, MD	11	MPa	ASTM D882
stress at yield, TD	18	MPa	ASTM D882
1% secant modulus, MD	260	MPa	ASTM D882
1% secant modulus, TD	290	MPa	ASTM D882
Tear Resistance			
MD	9	g/μm	ASTM D1922
TD	14	g/μm	ASTM D1922
THERMAL PROPERTIES			
Vicat Softening Temperature	92	°C	ASTM D1525