



SAFETY DATA SHEET

North America U.S. GHS Format

Print date: 24-Mar-2015

Revision Number: 2

Revision date: 25-Mar-2015

1. IDENTIFICATION OF THE SUBSTANCE AND COMPANY

Trademark:	LUBRICOMP™
Product Code:	WL003 - WHNAT
Product Description:	Poly (butylene terephthalate) [CASRN 30965-26-5]
Product Type:	Commercial Product
Recommended use:	May be used to produce molded or extruded articles or as a component of other industrial products.
Company:	SABIC Innovative Plastics US LLC One Plastics Avenue Pittsfield, MA 01201 USA (413) 448-5800 www.sabic-ip.com
Manufacturer:	SABIC Innovative Plastics US LLC 251 South Bailey Road Thorndale, Pennsylvania 19372 United States
Emergency Telephone Number:	800/447-4545
Emergency Transportation/CHEMTREC (24 HOUR):	800 424-9300 (USA) +1 703-527-3887 (globally, outside USA)
E-mail:	productinquiries@sabic-ip.com
Website Address:	www.sabic-ip.com



2. HAZARDS IDENTIFICATION

The additives in this product are bound in a thermoplastic resin matrix. In accordance with GHS for the classification of the product, the hazard potential may be assessed with respect to the physico-chemical form and/or bioavailability of the individual components in the thermoplastic resin.

Where GHS classifications are shown below, these are based on the individual components in the thermoplastic resin matrix. Under the typical use conditions for the resin, these hazardous components are unlikely to contribute to workplace exposure. Please read the entire safety data sheet and/or consult an EHS professional for a complete understanding.

Classification

OSHA Regulatory Status

This product is not considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

GHS-Labeling

Emergency Overview

Not classified

The product contains no substances which at their given concentration, are considered to be hazardous to health

Appearance: Pellets

Physical State: Solid

Odor: None

Hazards not otherwise classified (HNOC)

Not applicable

Other Information

Not applicable

Other hazards which do not result in classification:

SABIC Emergency Overview

- Pellets with slight or no odor
- Spilled material may create slipping hazard
- Can burn in a fire creating dense, toxic smoke
- Molten plastic can cause severe thermal burns
- Fumes produced during melt processing may cause eye, skin, and respiratory tract irritation. Severe over-exposure may result in nausea, headache, chills, and fever. See below for additional effects.
- Secondary operations, such as grinding, sanding, or sawing can produce dust which may present an explosion or respiratory hazard.

Other Information:

Cool skin rapidly with cold water after contact with molten material. Heating can release hazardous gases. Hazardous fumes can also occur in post-processing operations.

Processing Issues:

Processing vapors may cause irritation to the eyes, skin, and respiratory tract. In cases of severe exposure, nausea and headache can also occur. Grease-like processing vapor condensates on ventilation ductwork, molds, and other surfaces can cause irritation and injury to skin.

Aggravated Medical Conditions:

MEDICAL RESTRICTIONS: There are no known health effects aggravated by exposure to this product. However, certain sensitive individuals and individuals with respiratory impairments may be affected by exposure to components in the processing vapors.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Product Type Mixture

HAZARDOUS COMPONENTS:

Chemical Name	CAS Number	Weight %
Tetrahydrofuran	109-99-9	0.1 - 0.3

The non-hazardous components and exact percentage (concentration) of the composition have been withheld as a trade secret.

This product consists primarily of high molecular weight polymers which are not expected to be hazardous. The ingredients in this product are present within the polymer matrix and are not expected to be hazardous.

4. FIRST AID MEASURES

If Inhalation:	Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. Processing fumes inhalation may be irritating to the respiratory tract. If symptoms are experienced remove victim from source of contamination or move victim to fresh air and obtain medical advice. If symptoms persist, call a physician.
On skin contact:	Immediately cool the skin by rinsing with cold water after contact with hot material. Wash off immediately with soap and plenty of water. If skin irritation persists, call a physician.
On contact with eyes:	Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. If eye irritation persists, consult a specialist.
On ingestion:	Not probable due to nature of the product. If a large amount of pellet material is swallowed, consult a physician for medical treatment.
Precautions:	Cool molten product on skin with plenty of water. Do not remove solidified product. Do not peel polymer from the skin.

5. FIRE-FIGHTING MEASURES

Autoignition Temperature:	360°C (680°F), estimated
Explosive Properties:	Avoid generating and accumulating dusts; fine dust dispersed in air in sufficient concentrations, and in the presence of an ignition source is a potential dust explosion hazard.
Suitable Extinguishing Media:	Use dry chemical, CO ₂ , water spray or "alcohol" foam. Water is the best extinguishing medium. Carbon dioxide and dry chemical are not generally recommended because their lack of cooling capacity may permit re-ignition on larger resin fires (blobs, drools, etc.).
Unsuitable Extinguishing Media for Safety Reasons:	Do not use a solid water stream as it may scatter and spread fire.
Special Protective Equipment for Firefighters:	In the event of fire, wear self-contained breathing apparatus.
Specific Hazards:	Take precautionary measures against static discharges. During processing, dust may form explosive mixture in air. Thermal decomposition can lead to release of irritating gases and vapors.

6. ACCIDENTAL RELEASE MEASURES

Clean up:	Sweep up and shovel into suitable containers for disposal. Do not create a powder cloud by using a brush or compressed air.
Personal Precautions:	See section 8.
Environmental Precautions:	Do not flush into surface water or sanitary sewer system. Material should not be released into the environment.

7. HANDLING AND STORAGE

Handling:	Handle in accordance with good industrial hygiene and safety practices. Provide for appropriate exhaust ventilation and dust collection at machinery. Avoid dust formation. All metal parts of the mixing and processing equipment must be earthed. Handle in accordance with good industrial hygiene and safety practice for diagnostics.
Storage:	Store in closed container in a dry and cool area. Keep away from heat sources and sources of ignition. Keep in a dry place. Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep away from food and drink.
Incompatible Products:	No special restrictions on storage with other products.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure limits:

No components with information, unless noted below

Chemical Name	US OSHA PEL (8 Hr)	ACGIH	Canada - Alberta (8 Hr)	Mexico OEL Data	SABIC Recommend (8 Hr)*
Tetrahydrofuran 109-99-9	FRL_STEL: 735 mg/m ³ , 250 ppm ; FRL_TWA: 590 mg/m ³ , 200 ppm ; TL_PEL: 590 mg/m ³ , 200 ppm	STEL: 100 ppm ; TWA: 50 ppm ; Notations: Confirmed Animal Carcinogen with Unknown Relevance to Humans , Skin ; Crit Eff: CNS impairment , Kidney damage , Upper respiratory tract irritation	OEL_15 mins: 295 mg/m ³ , 100 ppm ; OEL_8 hr: 147 mg/m ³ , 50 ppm ; Substance interaction: SI_1	LMPE-PPT: 200 ppm , 590 mg/m ³ ; LMPE-CT: 250 ppm , 735 mg/m ³	50 ppm TWA

*SABIC Recommended Exposure Limits have been established for certain chemicals.

Engineering Measures to Exposure:

Handle in accordance with good industrial hygiene and safety practice. Provide for appropriate exhaust ventilation at machinery. Processing fume condensate may be a fire hazard and toxic; remove periodically from exhaust hoods, ductwork, and other surfaces using appropriate personal protection. Polybutyleneterephthalate fumes and condensates may contain trace quantities of tetrahydrofuran (typically less than 1 ppm, see section 2, 3 and 11).

Hand Protection:

Protective gloves should be worn

Eye Protection:

Safety glasses with side-shields.

Respiratory Protection:

When using this product at elevated temperatures, implement engineering systems, administrative controls or a respiratory protection program (including a respirator approved for protection from organic vapors, acid, gases, and particulate matter) if processing vapors are not adequately controlled or operators experience symptoms of overexposure. If dust or powder are produced from secondary operations such as sawing or grinding, use a respirator approved for protection from dust.

Body Protection:

Long sleeved clothing

Hygiene Measures:

When using, do not eat, drink or smoke.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State:	Solid
Appearance:	Pellets
Color:	Same as color code
Odor:	None
Odor Threshold:	No information available
pH	No data available
Boiling point/range:	Not determined
Melting point/range:	Various
Autoignition Temperature:	360°C (680°F) estimated
Flammability (solid, gas):	No information available
Vapor Pressure:	Negligible
Water Solubility:	Insoluble
Partition coefficient: (n-octanol/water)	No information available
Vapor Density:	Not determined
Evaporation Rate:	Negligible
Decomposition temp. (°C) :	Not determined
Specific gravity:	>1; (water = 1)
VOC content (%):	Negligible
Explosive Limits	
upper:	Not determined
lower:	Not determined

10. STABILITY AND REACTIVITY

Stability:	Stable under ambient conditions. Hazardous polymerization does not occur.
Conditions to Avoid:	Decomposition under influence of moisture is highly accelerated by heating. To avoid thermal decomposition, avoid elevated temperatures. Heating can result in the formation of gaseous decomposition products, some of which may be hazardous. Do not exceed melt temperature recommendations in product literature. Purgings of hot material should be collected in small, flat, thin shapes and quenched with water to allow for rapid cooling. Do not allow product to remain in barrel at elevated temperatures for extended periods of time.
Hazardous Decomposition Products:	Process vapors under recommended processing conditions may include trace levels of hydrocarbons, tetrahydrofuran (THF), aliphatic aldehydes, hydrogen fluoride, carbonyl fluoride, perfluorohydrocarbon fragments.
Incompatible Products:	None known

11. TOXICOLOGICAL INFORMATION

Acute Toxicity

LD50/oral/rat: >5000 mg/kg

LD50/dermal/rabbit: >2000 mg/kg

Inhalation: Pellet inhalation unlikely due to physical form. Processing fumes evolved at recommended processing conditions may contain trace amounts of tetrahydrofuran (typically less than 1 ppm). NTP has listed tetrahydrofuran as a carcinogen. Extreme processing conditions or temperatures may result in higher levels. See section 8 for appropriate exposure controls and personal protection.

Eye Contact: Resin particles, like other inert materials, are mechanically irritating to eyes.

Skin Contact: Not a hazard with pellets during normal industrial use.

Ingestion: Pellet ingestion unlikely due to physical form.

Chronic Toxicity: No information available.

Subchronic Toxicity: No information available

Primary Irritation: Substance does not generally irritate and is only mildly irritating to the skin.

OSHA: Not regulated

NTP: Tetrahydrofuran: In 2-year carcinogenicity bioassays conducted by the National Toxicology Program (NTP), mice and rats (50/sex/group) were exposed to concentrations of 0, 200, 600, or 1,800 ppm via inhalation 6 hours/day, 5 days/week for 104 weeks. Under the conditions of these 2-year inhalation studies, there was some evidence of carcinogenic activity of tetrahydrofuran in male F344/N rats based on increased incidences of renal tubule adenoma or carcinoma (combined) at 600 and 1,800 ppm. There was no evidence of carcinogenic activity of tetrahydrofuran in female F344/N rats exposed to 200, 600, or 1,800 ppm or male B6C3F1 mice exposed to 200, 600, or 1,800 ppm. There was clear evidence of carcinogenic activity of tetrahydrofuran in female B6C3F1 mice based on increased incidences of hepatocellular neoplasms observed at 1,800 ppm.

Remarks: The toxicological data has been taken from products of similar composition.

Special Studies: PROCESSING FUMES: Processing fumes evolved at recommended processing conditions may contain trace amounts of tetrahydrofuran (typically less than 1 ppm). Extreme processing conditions or temperatures may result in higher levels. See section 8 for appropriate exposure controls and personal protection. In 2-year carcinogenicity bioassays conducted by the National Toxicology Program (NTP), mice and rats (50/sex/group) were exposed to tetrahydrofuran at concentrations of 0, 200, 600, or 1,800 ppm via inhalation 6 hours/day, 5 days/week for 104 weeks. Under the conditions of these 2-year inhalation studies, there was some evidence of carcinogenic activity of tetrahydrofuran in male F344/N rats based on increased incidences of renal tubule adenoma or carcinoma (combined) at 600 and 1,800 ppm. There was no evidence of carcinogenic activity of tetrahydrofuran in female F344/N rats exposed to 200, 600, or 1,800 ppm or male B6C3F1 mice exposed to 200, 600, or 1,800 ppm. There was clear evidence of carcinogenic activity of tetrahydrofuran in female B6C3F1 mice based on increased incidences of hepatocellular neoplasms observed at 1,800 ppm. Thermal degradation of the fluoropolymer additives in this product may result in the release of pyrolysis products and fumes. Short term inhalation exposure may cause influenza-like symptoms such as chest pain/tightness, shortness of breath, sore throat, fever and chills, malaise and sometimes headache (also known as "polymer fume fever"). Following removal from exposure, complete resolution is expected within 12-48 hours. Prolonged and repeated exposure to high levels may lead to effects such as pulmonary edema and lung disease.

12. ECOLOGICAL INFORMATION

Ecotoxicity Effects:

Do not flush into surface water or sanitary sewer system.

Other information:

Ecological damages are not known or expected under normal use.

13. DISPOSAL CONSIDERATIONS

Contaminated Packaging:

Empty containers should be taken for local recycling, recovery or waste disposal.

Waste Disposal:

Recycling is encouraged. Landfill or incinerate in accordance with federal, state and local requirements. Collected processing fume condensates and incinerator ash should be tested to determine waste classification.

14. TRANSPORT INFORMATION

DOT

ADR/RID/ADN

IMDG

ICAO

IATA-DGR

MEXICO

CANADA/TDG

15. REGULATORY INFORMATION

International Inventories:

TSCA (USA):	Listed
DSL (Canada):	Listed
EINECS/ELINCS (Europe):	Listed
ENCS (Japan):	Listed
IECSC (China):	Listed
KECL (Korea):	Listed
PICCS (Philippines):	Listed
AICS (Australia):	Listed
NZIoC (New Zealand):	Listed



Other Inventory Information:

A "Listed" entry above means all chemical components are on the respective inventory list and/or a qualifying exemption exists for one or more components. A "Not listed" entry above indicates one or more components is restricted from import or manufacture into that country/region. Articles are exempt from registration and are therefore not listed on the national chemical inventories.

SVHC (REACH Regulation (EC) No 1907/2006 and 453/2010, as amended):

This product does not intentionally contain SVHC chemicals except as noted below. Incidental amounts of impurities, if present, would be below the threshold limit of 0.1% by weight.

SARA (313) Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA):

This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

SARA (311, 312) hazard class:

Acute Health Hazard	N
Chronic Health Hazard	N
Fire Hazard	N
Sudden Release of Pressure Hazard	N
Reactive Hazard	N

Canada - WHMIS Classification:

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all the information required by the CPR. Unless noted below, this product is non-controlled. Some classifications may not apply to the entire product.

California Proposition 65:

This product does not contain components known to the State of California to cause cancer and/or reproductive effects.

RoHS EU Directive 2011/65/EU:

The subject product is in compliance with EU RoHS Directive 2011/65/EU. All below chemicals are not employed in the manufacture of the product: a.Cadmium and its compounds, b.Lead and its compounds, c.Mercury and its compounds, d.Hexavalent chromium compounds, e.Polybrominated biphenyls (PBBs), f.Polybrominated diphenyl ethers (PBDEs including Deca-BDE). The trace levels of heavy metals may be present as impurities within threshold limits (<0.1% for Pb, Hg, Cr VI, and <0.01% for Cd). We are disclosing this information, to the best of our knowledge, based upon data from our raw material manufacturers.

HMIS Rating

Health: 0

Flammability: 1

Reactivity: 0

16. OTHER INFORMATION

SABIC and brands marked with TM are trademarks of SABIC or its subsidiaries or affiliates.

www.sabic-ip.com

<http://eur.sabic-ip.com/ordeur/pages/msds/MSDSSearch.jsp?app=sabic-ip>

SDS Scope:

USA: Conforms to 29 CFR 1910.1200 (2012 OSHA Hazard Communication Standard)

This document is also applicable in other countries and regions.

Prepared by: Product Stewardship & Toxicology

Reason for revision: Update to GHS format

DISCLAIMER: This Safety Data Sheet [SDS] information is provided based on the Hazard Communication Regulations for your region or country and for the use of the persons required to receive this information under those regulations. The information is neither designed nor recommended for any other use or for use by any other person, including for compliance with other laws. SABIC Innovative Plastics does not warrant the suitability for use of this SDS for any other material or product not specifically identified herein. SABIC Innovative Plastics does not warrant the accuracy or authenticity of this SDS unless it has been obtained directly from SABIC Innovative Plastics, or posted or viewed on a SABIC Innovative Plastics website. Modification of this SDS, unless specifically authorized by SABIC Innovative Plastics, is strictly prohibited. This SDS is based on information that is believed to be reliable, but may be subject to change as new information becomes available. Because it is not possible to anticipate all conditions of use, additional safety precautions may be required. Since the use of this material is not under SABIC Innovative Plastics' control, each user is responsible for making its own determination as to the safe and proper handling of this material in its own particular use of this material. SABIC INNOVATIVE PLASTICS MAKES NO REPRESENTATION OR WARRANTY, EITHER EXPRESS OR IMPLIED, INCLUDING AS TO MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Each user should read and understand this information and incorporate it into individual site safety programs as required by applicable hazard communication standards and regulations.

End of Safety Data Sheet