

# SAFETY DATA SHEET **Asia Pacific GHS Format**

Print date: 16-Apr-2013 Revision Number: 1 Revision date: 16-Apr-2013

## 1. IDENTIFICATION OF THE SUBSTANCE AND COMPANY

STATKON\* Trademark:

**Product Code:** DX13320C -BKNAT

**Product Description:** Proprietary Polycarbonate Ester

**Product Type:** Commercial Product

Recommended use: May be used to produce molded or extruded articles or as a component of other industrial

products.

Company: SABIC Innovative Plastics Japan LLC.

Tokyo Club Building, 2-6 3Chome Kasumigaseki, Chiyoda-Ku Tokyo, 100-0013 Japan SABIC Innovative Plastics (China) Ltd.or SABIC Innovative Plastics International Trading Shanghai Ltd 16F, Plaza 66, No 1266 Nanjing Rd(W), Shanghai 200040 China(Contact

address)

SABIC Innovative Plastics Korea, Ltd.

Donghoon Bldg, 20fl, 702-19, Yeoksam-Dong, Kangnam-Ku, Seoul, Korea

SABIC Innovative Plastics Singapore Pte Ltd

23, Benoi Road, 629895 Singapore

SABIC Innovative Plastics (Thailand) Co. Ltd

64/22 Moo 4 Tumbol Pluak Daeng, Amphur Pluak Daeng, Rayong 21140 Thailand

Sabic Innivative Plastics India Ltd.

Plastics Avenue, P.O. Jawaharnagar, District Vadodara 391320 India

SABIC Innovative Plastics Taiwan Holding Limited,

Room B,7F,No. 8,Min-Sheng E. Rd. Sec. 3,Taipei City 10480 Taiwan

Manufacturer: SABIC Innovative Plastics Singapore Pte Ltd

> 23, Benoi Road Singapore 629895

Telephone: (65) 6 210 4273 Fax: (65) 6 210 4267

**Emergency Telephone Number:** 

Japan: +(81)-3-3593-4735 China: +86 532 83889090,+86 20 84980148

Singapore: +(65)-6210 4199

Korea: +(82)-2-510-6546

Thailand: +(66)-22312323-4 ext. 46, +(66)-38927000 ext. 7026

India: +(91)-265 3068554

**Emergency** 

800 424-9300 (USA)

Transportation/CHEMTREC (24 HOUR):

+1 703-527-3887 (globally, outside USA)

E-mail:

Asiaproductinquiries@sabic-ip.com

Website Address:

www.sabic.com

Product Name: DX13320C-BKNAT Page 1 of 9 Revision date: 16-Apr-2013



## 2. HAZARDS IDENTIFICATION

The additives in this product are bound in a thermoplastic resin matrix. In accordance with GHS for the classification of the product, the hazard potential may be assessed with respect to the physico-chemical form and/or bioavailability of the individual components in the thermoplastic resin.

Where GHS classifications are shown below, these are based on the individual components in the thermoplastic resin matrix. Under the typical use conditions for the resin, these hazardous components are unlikely to contribute to workplace exposure. Please read the entire safety data sheet and/or consult an EHS professional for a complete understanding.

Globally Harmonized System, UN(GHS) - Classification

**GHS Category** 

Not hazardous

Not classified

**GHS-Labeling** 

GHS Labeling not required

#### **Precautionary Statements**

No GHS specific Precautionary Statements required - observe all other warnings and handling instructions in this SDS.

Other hazards which do not result in classification:

Product Name: DX13320C-BKNAT Page 2 of 9 Revision date: 16-Apr-2013



### **SABIC Emergency Overview**

- Pellets with slight or no odor
- · Spilled material may create slipping hazard
- · Can burn in a fire creating dense, toxic smoke
- Molten plastic can cause severe thermal burns
- Fumes produced during melt processing may cause eye, skin, and respiratory tract irritation. Severe over-exposure may result in nausea, headache, chills, and fever. See below for additional effects.
- · Secondary operations, such as grinding, sanding, or sawing can produce dust which may present an explosion or respiratory hazard.

Other Information: OSHA, IARC and/or NTP have listed carbon, titanium dioxide, crystalline silica (quartz),

respirable glass and certain heavy metals, present in some colorants and fillers, as carcinogens. If these materials are present in this product at significant quantities, they are shown in Section 2/3. These materials are essentially bound to the plastic matrix and are unlikely to contribute to workplace exposure under recommended processing conditions.

Processing Issues: Processing vapors may cause irritation to the eyes, skin, and respiratory tract. In cases of

severe exposure, nausea and headache can also occur. Grease-like processing vapor condensates on ventilation ductwork, molds, and other surfaces can cause irritation and injury

to skin.

Aggravated Medical Conditions: MEDICAL RESTRICTIONS: There are no known health effects aggravated by exposure to this

product. However, certain sensitive individuals and individuals with respiratory impairments

may be affected by exposure to components in the processing vapors.

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

Product Type Mixture

This product consists primarily of high molecular weight polymers which are not expected to be hazardous. The ingredients in this product are present within the polymer matrix and are not expected to be hazardous.

## 4. FIRST AID MEASURES

If Inhalation: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. If

symptoms persist, call a physician.

On skin contact: Immediately cool the skin by rinsing with cold water after contact with hot material. Wash off

immediately with soap and plenty of water. Consult a physician.

On contact with eyes: Immediately flush with plenty of water. After initial flushing, remove any contact lenses and

continue flushing for at least 15 minutes. If eye irritation persists, consult a specialist.

On ingestion: No hazards which require special first aid measures.

**Precautions:** Processing vapors inhalation may be irritating to the respiratory tract. If symptoms are

experienced remove victim from the source of contamination or move victim to fresh air and

obtain medical advice.

## **5. FIRE-FIGHTING MEASURES**

Autoignition Temperature: 630°C (1166°F) estimated

Product Name: DX13320C-BKNAT Page 3 of 9 Revision date: 16-Apr-2013



Suitable Extinguishing Media: Use dry chemical, CO2, water spray or "alcohol" foam. Water is the best extinguishing

medium. Carbon dioxide and dry chemical are not generally recommended because their lack

of cooling capacity may permit re-ignition on larger resin fires (blobs, drools, etc.).

Unsuitable Extinguishing Media for Safety Reasons:

Do not use a solid water stream as it may scatter and spread fire.

**Hazards from Combustion** 

Products:

Fire will produce dense black smoke containing hazardous combustion products, carbon

oxides, hydrocarbon fragments.

**Specific Hazards:** Take precautionary measures against static discharges. During processing, dust may form

explosive mixture in air. Thermal decomposition can lead to release of irritating gases and

vapors.

Special Protective Equipment

for Firefighters:

Do not enter fire area without proper protection including self-contained breathing apparatus and full protective equipment. Fight fire from a safe distance and a protected location due to

the potential of hazardous vapors and decomposition products.

**Exposure hazards:** Do not release chemically contaminated water into drains, soil or surface water. Sufficient

measures must be taken to retain the water used for extinguishing. Dispose of contaminated

water and soil according to local regulations.

### 6. ACCIDENTAL RELEASE MEASURES

Personal Precautions: See section 8.

Environmental Precautions: Do not flush into surface water or sanitary sewer system. Material should not be released into

the environment.

Clean up: Sweep up and shovel into suitable containers for disposal. Do not create a powder cloud by

using a brush or compressed air.

## 7. HANDLING AND STORAGE

Handle in accordance with good industrial hygiene and safety practices Provide for appropriate

exhaust ventilation and dust collection at machinery Avoid dust formation All metal parts of the

mixing and processing equipment must be earthed

Storage: Store in closed container in a dry and cool area. Keep away from heat sources and sources of

ignition. Keep away from food, drink and animal feeding stuffs. Keep container tightly closed in

a dry and well-ventilated place.

Incompatible Products: Strong acids, strong oxidizing agents.

### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure limits: No components with information, unless noted below

\*SABIC Recommended Exposure Limits have been established for certain chemicals.

Engineering Measures to Reduce Exposure:

Handle in accordance with good industrial hygiene and safety practice. Provide for appropriate exhaust ventilation at machinery. Processing fume condensate may be a fire hazard and toxic; remove periodically from exhaust hoods, ductwork, and other surfaces using appropriate

personal protection.

**Hand Protection:** Protective gloves should be worn

Product Name: DX13320C-BKNAT Page 4 of 9 Revision date: 16-Apr-2013



**Eye Protection:** Safety glasses with side-shields or chemical goggles. In addition, use full-face shield when

cleaning processing vapor condensates from hood, ducts, and other surfaces.

When using this product at elevated temperatures, implement engineering systems, **Respiratory Protection:** 

> administrative controls or a respiratory protection program (including a respirator approved for protection from organic vapors, acid, gases, and particulate matter) if processing vapors are not adequately controlled or operators experience symptoms of overexposure. If dust or powder are produced from secondary operations such as sawing or grinding, use a respirator

approved for protection from dust.

**Body Protection:** Long sleeved clothing

**Hygiene Measures:** When using, do not eat, drink or smoke.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

Solid **Physical State:** Appearance: Pellets

Color: Same as color code Odor: None or slight

Melting point/range: This product does not exhibit a sharp melting point but softens gradually over a wide range of

temperatures.

Flash Point: Not applicable **Evaporation Rate:** Negligible

**Explosive Limits** 

upper: Not determined lower: Not determined Vapor Pressure: Negligible >1; (water = 1)

Specific gravity: Water Solubility: Insoluble

**Autoignition Temperature:** 630°C (1166°F) estimated

Dust may form explosive mixture in air **Explosive Properties:** 

**Oxidising Properties:** Not oxidising VOC content (%): Negligible

# 10. STABILITY AND REACTIVITY

Reactivity: Not reactive under recommended conditions of handling, storage,

processing and use.

Stability: Stable under ambient conditions. Hazardous polymerization does

not occur.

Polymerization: Hazardous polymerization does not occur.

**Conditions to Avoid:** Avoid temperatures above 630°C. To avoid thermal decomposition,

avoid elevated temperatures. Heating can result in the formation of

gaseous decomposition products, some of which may be

hazardous. Do not exceed melt temperature recommendations in product literature. Purgings of hot material should be collected in small, flat, thin shapes and quenched with water to allow for rapid cooling. Do not allow product to remain in barrel at elevated

temperatures for extended periods of time.

Product Name: DX13320C-BKNAT Page 5 of 9 Revision date: 16-Apr-2013



Materials to Avoid: May react with strong oxidizing agents, strong acids or other highly

reactive chemicals.

Hazardous Decomposition Products: Process vapors under recommended processing conditions may

include trace levels of hydrocarbons, phenols, alkylphenols,

diarylcarbonates.

## 11. TOXICOLOGICAL INFORMATION

**Acute Toxicity** 

**Product Information:** 

**LD50/oral/rat**: >5000 mg/kg **LD50/dermal/rabbit**: >2000 mg/kg

**Component Information:** 

Component Information Text: No data available

Sensitization

Respiratory Sensitization: Not classified

Irritation:

Eye Irritation: no data available

**Subchronic Toxicity (28 days)** 

Repeated Oral Toxicity(28d):

Repeated Dermal Toxicity(28d):

Subchronic Toxicity:

No information available
No information available
No information available

**Chronic Toxicity** 

Carcinogenicity: There are no known carcinogenic chemicals in this product except

specifically mentioned below.

Mutagenic Effects: No data is available on the product itself

Reproductive Toxicity:No information availableDevelopmental Toxicity:No information available

Neurological effects: No information available

Specific Target Organ Toxicity(STOT)

Target Organ Effects: Not established

**Aspiration Hazard** 

Aspiration Hazard Statement: No data available

Other relevant toxicity information

IARC: Not listed
OSHA: Not regulated
NTP: Not tested

**Remarks:** The toxicological data has been taken from products of similar

composition.

Special Studies: No Information

Product Name: DX13320C-BKNAT Page 6 of 9 Revision date: 16-Apr-2013



## 12. ECOLOGICAL INFORMATION

**Ecotoxicity** 

**Component Information:** 

99.605% of the mixture consists of components(s) of unknown hazards to the aquatic environment.

**Product Information:** 

**Persistence and Degradability** 

Biodegradation: Not inherently biodegradable

Partition coefficient (n-octanol/water)

Not established

**Bioaccumulative Potential:** 

Bioaccumulation: Not established

Mobility

Mobility: May be separated mechanically in waste water plants.

**Other Adverse Effects** 

**Ecotoxicity Effects:** Do not flush into surface water or sanitary sewer system.

# 13. DISPOSAL CONSIDERATIONS

Waste from residues / unused Where possible recycling is preferred to disposal or incineration. Dispose of in accordance with

**products:** local regulations.

Contaminated Packaging: Empty containers should be transported/delivered using a registered waste carrier for local

recycling or waste disposal.

Waste Disposal: Recycling is encouraged. Landfill or incinerate in accordance with federal, state and local

requirements. Collected processing fume condensates and incinerator ash should be tested to

determine waste classification.

## 14. TRANSPORT INFORMATION

IMO / IMDG Not regulated

ICAO Not regulated

IATA-DGR Not regulated

**DOT** Not regulated

ADR/RID Not regulated

ADR Not regulated

ADN Not regulated

Product Name: DX13320C-BKNAT Page 7 of 9 Revision date: 16-Apr-2013



## 15. REGULATORY INFORMATION

**International Inventories:** 

TSCA (USA): Listed

**DSL (Canada):** Listed - use of a substance in this product in any quantity in baby bottles or food packaging

materials intended for infants or newborns up to 18 months of age is restricted by Environment

Canada under a Significant New Activity (SNAc) Notice.

EINECS/ELINCS (Europe): Listed

ENCS (Japan): Not listed - Full notification approved under Sabic Innovative Plastics

IECSC (China): Listed - Polymer simplified notification approved under Sabic Innovative Plastics

**KECL (Korea):** Listed - Full notification approved under Sabic Innovative Plastics

PICCS (Philippines): Not listed - Polymer exempted, in compliance

AICS (Australia): Not listed NZIOC (New Zealand): Not listed

### Other Inventory Information:

A "Listed" entry above means all chemical components are on the respective inventory list and/or a qualifying exemption exists for one or more components. A "Not listed" entry above indicates one or more components is restricted from import or manufacture into that country/region. Articles are exempt from registration and are therefore not listed on the national chemical inventories.

## SARA (313) Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA)

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

#### **SARA (311, 312) hazard class:**

Acute Health Hazard

Chronic Health Hazard

Fire Hazard

Sudden Release of Pressure Hazard

N
Reactive Hazard

N

#### Canada:

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.

#### WHMIS hazard class:

Non-controlled

#### California Proposition 65:

This product does not contain components known to the State of California to cause cancer and/or reproductive effects.

# RoHS EU Directive 2002/95/EC:

The subject product is in compliance with EU RoHS Directive 2002/95/EC. All below chemicals are not employed in the manufacture of the product: a.Cadmium and its compounds, b.Lead and its compounds, c.Mercury and its compounds, d.Hexavalent chromium compounds, e.Polybrominated biphenyls (PBBs), f.Polybrominated diphenyl ethers (PBDEs including Deca-BDE). The trace levels of heavy metals may be present as impurities within threshold limits (<0.1% for Pb, Hg, Cr VI, and <0.01% for Cd). We are disclosing this information, to the best of our knowledge, based upon data from our raw material manufacturers.

#### Remarks:

This product consists primarily of high molecular weight polymers which are not expected to be hazardous. The ingredients in this product are present within the polymer matrix and are not expected to be hazardous.

Product Name: DX13320C-BKNAT Page 8 of 9 Revision date: 16-Apr-2013



HMIS Rating Health: 0 Flammability: 1 Reactivity: 0

## **16. OTHER INFORMATION**

STATKON\* is a trademark of SABIC Innovative Plastics IP BV

#### SDS Scope:

China: Conforms to Chinese Regulation on the Control over Safety of Hazardous Chemicals (Decree No 591) and GHS standards GB15258,GB13698,GB/T16483 etc.

Japan: Conforms to Industrial Safety and Health Law, Japan (2006) and Industrial GHS Standards JIS Z7250, JIS Z7251

Korea: Conforms to Industrial Safety & Health Act, Ministry of Labor, Korea

Singapore: Conforms to Singapore workplace Safety and Health (WSH) Act, WSH Regulations, and GHS Standard 586 Taiwan: Conforms to Taiwan Rules on Hazard Communication and Labeling of Hazardous Substances, (Council of Labor Affairs, Taiwan) and GHS standards Z1051

Thailand: Conforms to Notification of the Ministry of Industry on the System of Classification and Hazard Communication of Hazardous Substances B.E. 2555 (2012)

This document is also applicable in other countries and regions.

#### Prepared by: Product Stewardship & Toxicology

DISCLAIMER: This Safety Data Sheet [SDS] information is provided based on the Hazard Communication Regulations for your region or country and for the use of the persons required to receive this information under those regulations. The information is neither designed nor recommended for any other use or for use by any other person, including for compliance with other laws. SABIC Innovative Plastics does not warrant the suitability for use of this SDS for any other material or product not specifically identified herein. SABIC Innovative Plastics does not warrant the accuracy or authenticity of this SDS unless it has been obtained directly from SABIC Innovative Plastics, or posted or viewed on a SABIC Innovative Plastics website. Modification of this SDS, unless specifically authorized by SABIC Innovative Plastics, is strictly prohibited. This SDS is based on information that is believed to be reliable, but may be subject to change as new information becomes available. Because it is not possible to anticipate all conditions of use, additional safety precautions may be required. Since the use of this material is not under SABIC Innovative Plastics' control, each user is responsible for making its own determination as to the safe and proper handling of this material in its own particular use of this material. SABIC INNOVATIVE PLASTICS MAKES NO REPRESENTATION OR WARRANTY, EITHER EXPRESS OR IMPLIED, INCLUDING AS TO MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Each user should read and understand this information and incorporate it into individual site safety programs as required by applicable hazard communication standards and regulations.

**End of Safety Data Sheet** 

Product Name: DX13320C-BKNAT Page 9 of 9 Revision date: 16-Apr-2013