

SAFETY DATA SHEET According to Regulation (EC) No 1907/2006 and 453/2010 (REACH)

Print date: 24-Mar-2015 Revision Number: 1 Revision date: 24-Mar-2015

1. IDENTIFICATION OF THE SUBSTANCE AND COMPANY

Trademark:	THERMOCOMP™
Product Code:	DX13006-GY5G154-0-RDV
Product Description:	Polycarbonate [CASRN 111211-39-3], glass fiber filled
Product Type:	Commercial Product
Recommended use:	May be used to produce molded or extruded articles or as a component of other industrial products.
Company:	SABIC Innovative Plastics B.V. Plasticslaan 1 P.O. Box 117 4600 AC Bergen op Zoom The Netherlands
Manufacturer:	SABIC Innovative Plastics Ottergeerde 22-28 4941 VM Raamsdonksveer The Netherlands
Emergency Telephone Number:	Bergen op Zoom +31(0)164-292911 (24/24)
Emergency Transportation/CHEMTREC (24 HOUR):	800 424-9300 (USA) +1 703-527-3887 (globally, outside USA)
E-mail:	webinquiries@sabic-ip.com
Website Address:	www.sabic-ip.com

Product Name: DX13006-GY5G154 Page 1 of 9 Revision date: 24-Mar-2015



2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW:

- · Pellets with slight or no odor
- · Spilled material may create slipping hazard
- · Can burn in a fire creating dense, toxic smoke
- Molten plastic can cause severe thermal burns
- Fumes produced during melt processing may cause eye, skin, and respiratory tract irritation. Severe over-exposure may result in nausea, headache, chills, and fever. See below for additional effects.
- Secondary operations, such as grinding, sanding, or sawing can produce dust which may present an explosion or respiratory hazard.

Skin Contact: Not a hazard with pellets during normal industrial use. Contact

causes skin irritation.

Eye Contact: Resin particles, like other inert materials, are mechanically

irritating to eyes.

Inhalation: Pellet inhalation unlikely due to physical form. Irritating to

respiratory system; avoid inhalation of dusts.

Ingestion: Pellet ingestion unlikely due to physical form.

Other Information: Cool skin rapidly with cold water after contact with molten

material. Heating can release hazardous gases. Hazardous

fumes can also occur in post-processing operations.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Not a hazardous substance or preparation according to EC-directives 1999/45/EC and 1272/2008/EC unless indicated.

HAZARDOUS COMPONENTS:

Chemical Name	CAS Number	ELINCS / EINECS-No.:	Weight %	Classification
Fiberglass, EU/GHS classified	65997-17-3	266-046-0	10-30	Classification: Carc.Cat.3; R40
Titanium dioxide	13463-67-7	236-675-5	0.3-1.0	R23-33-36/37/38/25-29

Chemical Name	SABIC Recommend (8 Hr)*	MAC (15 min. TWA)	MAC (8hr TWA)
Titanium dioxide	Not established	10 MGM3 Inhalable dust.	10 mg/m ³ 5 MG/M3
		5 MGM3 Respirable dust.	(resp.dust)

Remarks:

This product consists primarily of high molecular weight polymers which are not expected to be hazardous. The ingredients in this product are present within the polymer matrix and are not expected to be hazardous.

Product Name: DX13006-GY5G154 Page 2 of 9 Revision date: 24-Mar-2015



4. FIRST AID MEASURES

If Inhalation: Move to fresh air in case of accidental inhalation of fumes from

overheating or combustion. Processing fumes inhalation may be irritating to the respiratory tract. If symptoms are experienced remove victim from source of contamination or move victim to fresh air and obtain medical advice. If symptoms persist, call a

physician.

On skin contact: Cool skin rapidly with cold water after contact with molten

polymer. Wash off immediately with soap and plenty of water. If

skin irritation persists, call a physician.

On contact with eyes: Immediately flush with plenty of water. After initial flushing,

remove any contact lenses and continue flushing for at least 15

minutes. If eye irritation persists, consult a specialist.

On ingestion: No hazards which require special first aid measures.

Precautions: Cool molten product on skin with plenty of water. Do not remove

solidified product. Do not peel polymer from the skin.

5. FIRE-FIGHTING MEASURES

Autoignition Temperature: 630°C (1166°F) estimated

Explosive Limits

upper: Not determined

lower: Not determined

Suitable Extinguishing Media: Use dry chemical, CO2, water spray or "alcohol" foam. Water is

the best extinguishing medium. Carbon dioxide and dry chemical are not generally recommended because their lack of cooling capacity may permit re-ignition on larger resin fires (blobs, drools,

etc.).

Unsuitable Extinguishing Media for Safety Reasons: Do not use a solid water stream as it may scatter and spread fire.

Hazardous Decomposition Products: Fire will produce dense black smoke containing hazardous

combustion products, carbon oxides, hydrocarbons fragments.

Special Protective Equipment for Firefighters: In the event of fire, wear self-contained breathing apparatus.

Specific Hazards: Take precautionary measures against static discharges. During

processing, dust may form explosive mixture in air. Thermal decomposition can lead to release of irritating gases and vapors.

6. ACCIDENTAL RELEASE MEASURES

Clean up: Sweep up and shovel into suitable containers for disposal. Do not

create a powder cloud by using a brush or compressed air.

Personal Precautions: See section 8.

Environmental Precautions: Do not flush into surface water or sanitary sewer system. Material

should not be released into the environment.

Product Name: DX13006-GY5G154 Page 3 of 9 Revision date: 24-Mar-2015



7. HANDLING AND STORAGE

Handling: Handle in accordance with good industrial hygiene and safety practices. Provide for

appropriate exhaust ventilation and dust collection at machinery. Avoid dust formation. All

metal parts of the mixing and processing equipment must be earthed.

Storage: Store in closed container in a dry and cool area. Keep away from

heat sources and sources of ignition.

Product Name: DX13006-GY5G154 Page 4 of 9 Revision date: 24-Mar-2015



8. EXPOSURE CONTROLS / PERSONAL PROTECTION

No components with information, unless noted below **Exposure limits:**

Chemical Name Fiberglass, EU/GHS classified

65997-17-3 **EU TWA** 5 mg/m³

Netherlands OEL - MAC 10 MGM3 Dust.

2 MGM3 Respirable dust.

2 FIBERS/CM3 Respirable fibers.

UK EH40 MEL (TWA)

WEL_TWA: 1 mg/m3 as W; WEL_STEL: 3 mg/m3 as W Spain - Valores Limite Ambientales - VLE

1FIBERS/CM3

0.5FIBERS/CM3

Switzerland SUVA Limit Values at the Workplace Data -

Time Weighted Average (TWA):

Norway Exposure Limit Values Data - Threshold Limit

Value:

Ireland Exposure Limit Values Data - Time Weighted

Italy - OEL

Average (TWA):

1 FIBERS/CM3 Fiber.

Chemical Name

France INRS (VME) **Netherlands OEL - MAC UK EH40 MEL (TWA)**

Spain - Valores Limite Ambientales - VLE

Denmark TWA Data - Threshold Limit Values (TLV):

Switzerland SUVA Limit Values at the Workplace Data -

Time Weighted Average (TWA):

Sweden Threshold Limit Values Data -

Portugal - TWAs

Norway Exposure Limit Values Data - Threshold Limit

Ireland Exposure Limit Values Data - Time Weighted

Average (TWA): **Greece - OEL**

Italy - OEL Poland - OEL:TWAs

Hand Protection:

Kol_C: k_1C; Comments: No data

KONS: 5 mg/m3 totalstøv

TWA 5 mg/m³, 1 fibres/cm3 of air

0.2 FIBERS/CM3 Fiber. 5 MGM3 Inhalable fraction.

Titanium dioxide 13463-67-7 10 MGM3 Τi 10 MGM3

WEL_TWA: 4 mg/m³ respirable, 10 mg/m³ total inhalable

VLA-ED: 10 mg/m³

GR: 6 mg/m3 beregnet som Ti

MAK_Wert: 3 mg/m³ alveolengangiger; Kol_SS: Grp_C

NGV: 5 MGM3 totaldamm

VLE-MP: 10 mg/m3; NOT: A 4; FUND: Pulmão

KONS: 5 mg/m3

TWA 4 mg/m³ respirable dust, 10 mg/m³ total inhalable dust

DT_1 5 mg/m³ T_1, 10 mg/m³ T_3

Protective gloves should be worn.

10 MGM3 10 mg/m³ NDS

Engineering Measures to Exposure:

In the case of hazardous fumes, wear self-contained breathing apparatus. Wear face-shield and protective suit for abnormal processing problems. Handle in accordance with good industrial hygiene and safety practice. Provide for appropriate exhaust ventilation at machinery. Handle in accordance with good industrial hygiene and safety practice for diagnostics. Provide appropriate exhaust ventilation at machinery and at places where dust can be generated.

Eye Protection: Safety glasses with side-shields.

Respiratory Protection: In the case of hazardous fumes, wear self contained breathing

apparatus. In case of insufficient ventilation wear suitable

respiratory equipment.

Product Name: DX13006-GY5G154 Page 5 of 9 Revision date: 24-Mar-2015

^{*}SABIC Recommended Exposure Limits have been established for certain chemicals.



Body Protection: Long sleeved clothing

Hygiene Measures: When using, do not eat, drink or smoke.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State: Solid Appearance: Pellets

Color: Same as color code

Odor: None

Melting point/range: This product does not exhibit a sharp melting point but softens

gradually over a wide range of temperatures.

Autoignition Temperature: 630°C (1166°F) estimated

Vapor Pressure: Negligible

Water Solubility: Insoluble Evaporation Rate: Negligible

Specific gravity: >1; (water = 1)
VOC content (%): Negligible

Explosive Limits

upper:Not determinedlower:Not determined

10. STABILITY AND REACTIVITY

Stability: Stable under ambient conditions. Hazardous polymerization does

not occur.

Conditions to Avoid: Avoid temperatures above 630°C. To avoid thermal

decomposition, avoid elevated temperatures. Heating can result in the formation of gaseous decomposition products, some of

which may be hazardous.

Hazardous Decomposition Products: Traces of phenol, alkylphenols, diarylcarbonates, .

Product Name: DX13006-GY5G154 Page 6 of 9 Revision date: 24-Mar-2015



11. TOXICOLOGICAL INFORMATION

LD50/oral/rat: >5000 mg/kg

LD50/dermal/rabbit: >2000 mg/kg

Subchronic Toxicity: No information available

Primary Irritation: Substance does not generally irritate and is only mildly irritating

to the skin. Skin irritation.

Remarks: The toxicological data has been taken from products of similar

composition.

Special Studies: Titanium Dioxide: The International Agency for Research on

Cancer (IARC) has determined titanium dioxide to be a possible human carcinogen (class 2B) based on evidence in experimental animals. Rats exposed to high doses of titanium dioxide by inhalation or intratracheal instillation showed an increased

incidence of lung tumors.

12. ECOLOGICAL INFORMATION

Ecotoxicity Effects: Do not flush into surface water or sanitary sewer system.

Ecotoxicity - Invertebrate Data: Ecological damages are not known or expected under normal

use.

13. DISPOSAL CONSIDERATIONS

Waste from residues / unused products: Where possible recycling is preferred to disposal or incineration.

Dispose of in accordance with local regulations.

EWC waste disposal no: 702 - waste from the manufacture, formulation, supply and use of

plastics, synthetic rubber and man-made fibres.

14. TRANSPORT INFORMATION

Transport Classification: Not regulated as hazardous for shipment, unless noted below,

under current transportation guidelines.

DOT

ADR/RID/ADN

<u>IMDG</u>

ICAO

IATA-DGR

Product Name: DX13006-GY5G154 Page 7 of 9 Revision date: 24-Mar-2015



15. REGULATORY INFORMATION

This substance is classified and labelled according to Annex I of Directive 67/548/EEC, as amended.

International Inventories:

TSCA (USA): Listed DSL (Canada): Listed **EINECS/ELINCS (Europe):** Listed ENCS (Japan): Listed IECSC (China): Listed **KECL** (Korea): Listed PICCS (Philippines): Not listed AICS (Australia): Listed NZIoC (New Zealand): Listed

REACH Information: For this product's REACH related information, please contact webinquiries@sabic-ip.com

Other Inventory Information:

A "Listed" entry above means all chemical components are on the respective inventory list and/or a qualifying exemption exists for one or more components. A "Not listed" entry above indicates one or more components is restricted from import or manufacture into that country/region. Articles are exempt from registration and are therefore not listed on the national chemical inventories.

SVHC (REACH Regulation (EC) No 1907/2006 and 453/2010, as amended):

This product does not intentionally contain SVHC chemicals except as noted below. Incidental amounts of impurities, if present, would be below the threshold limit of 0.1% by weight.

California Proposition 65:

Components in this product known to the State of California to cause cancer and/or reproductive effects, are listed below:

Chemical Name	Weight %	California Proposition 65:
Fiberglass, EU/GHS classified 65997-17-3	10-30	Listed: July 1, 1990 Carcinogenic. (airborne, unbound particles of respirable size)
Titanium dioxide 13463-67-7	0.3-1.0	Listed: September 2, 2011 Carcinogenic. (airborne, unbound particles of respirable size)
cobalt-nickel-zinc-titanium dioxide spinel 68186-85-6	0.1-0.3	Listed: May 7, 2004 Carcinogenic. (as nickel compounds)
Carbon black 1333-86-4	<100 ppm	Listed: February 21, 2003 Carcinogenic. (airborne, unbound particles of respirable size)

RoHS EU Directive 2011/65/EU:

The subject product is in compliance with EU RoHS Directive 2011/65/EU. All below chemicals are not employed in the manufacture of the product: a.Cadmium and its compounds, b.Lead and its compounds, c.Mercury and its compounds, d.Hexavalent chromium compounds, e.Polybrominated biphenyls (PBBs), f.Polybrominated diphenyl ethers (PBDEs including Deca-BDE). The trace levels of heavy metals may be present as impurities within threshold limits (<0.1% for Pb, Hg, Cr VI, and <0.01% for Cd). We are disclosing this information, to the best of our knowledge, based upon data from our raw material manufacturers.

Product Name: DX13006-GY5G154 Page 8 of 9 Revision date: 24-Mar-2015



16. OTHER INFORMATION

SABIC and brands marked with [™] are trademarks of SABIC or its subsidiaries or affiliates.

www.sabic-ip.com

http://eur.sabic-ip.com/ordeur/pages/msds/MSDSSearch.jsp?app=sabic-ip

SDS Scope:

Europe: Conforms to Regulation (EC) No 1907/2006 and 453/2010 (REACH)

This document is also applicable in other countries and regions.

Prepared by: Product Stewardship & Toxicology

DISCLAIMER: This Safety Data Sheet [SDS] information is provided based on the Hazard Communication Regulations for your region or country and for the use of the persons required to receive this information under those regulations. The information is neither designed nor recommended for any other use or for use by any other person, including for compliance with other laws. SABIC Innovative Plastics does not warrant the suitability for use of this SDS for any other material or product not specifically identified herein. SABIC Innovative Plastics does not warrant the accuracy or authenticity of this SDS unless it has been obtained directly from SABIC Innovative Plastics, or posted or viewed on a SABIC Innovative Plastics website. Modification of this SDS, unless specifically authorized by SABIC Innovative Plastics, is strictly prohibited. This SDS is based on information that is believed to be reliable, but may be subject to change as new information becomes available. Because it is not possible to anticipate all conditions of use, additional safety precautions may be required. Since the use of this material is not under SABIC Innovative Plastics' control, each user is responsible for making its own determination as to the safe and proper handling of this material in its own particular use of this material. SABIC INNOVATIVE PLASTICS MAKES NO REPRESENTATION OR WARRANTY, EITHER EXPRESS OR IMPLIED, INCLUDING AS TO MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Each user should read and understand this information and incorporate it into individual site safety programs as required by applicable hazard communication standards and regulations.

End of Safety Data Sheet

Product Name: DX13006-GY5G154 Page 9 of 9 Revision date: 24-Mar-2015