



## SAFETY DATA SHEET

### North America U.S. GHS Format

Print date: 09-May-2016

Revision Number: 3

Revision date: 09-May-2016

#### 1. IDENTIFICATION OF THE SUBSTANCE AND COMPANY

**Trademark:** CYCOLAC™  
**Product Code:** DL200H - BK1G489

**Product Description:** Modified Poly (acrylonitrile-butadiene-styrene)  
[CASRN 9010-94-0]/Poly (styrene-acrylonitrile)  
[CASRN 9003-54-7] blend

**Product Type:** Commercial Product

**Recommended use:** May be used to produce molded or extruded articles or as a component of other industrial products.

**Company:** SABIC Innovative Plastics US LLC  
One Plastics Avenue  
Pittsfield, MA 01201 USA  
(413) 448-5800  
www.sabic.com

**Manufacturer:** SABIC Innovative Plastics US LLC  
State Route 892 South  
Washington, West Virginia 26181  
United States

**Emergency Telephone Number:** 800-424-9300

**Emergency Transportation/CHEMTREC (24 HOUR):** 800 424-9300 (USA)  
+1 703-527-3887 (globally, outside USA)

**E-mail:** productinquiries@sabic.com  
**Website Address:** www.sabic.com

## 2. HAZARDS IDENTIFICATION

The additives in this product (if any) are bound in a thermoplastic resin matrix. In accordance with GHS for the classification of the product, the hazard potential may be assessed with respect to the physico-chemical form and/or bioavailability of the individual components in the thermoplastic resin.

Where GHS classifications are shown below, these are based on the individual components in the thermoplastic resin matrix. Under the typical use conditions for the resin, these hazardous components are unlikely to contribute to workplace exposure. Please read the entire safety data sheet and/or consult an EHS professional for a complete understanding.

### Classification

#### **OSHA Regulatory Status**

This product is not considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

In 1995, the International Agency for Research on Cancer (IARC) concluded that there is "sufficient evidence in experimental animals for the carcinogenicity of carbon black." IARC's overall evaluation was that "Carbon black is possibly carcinogenic to humans (2B)." In 2006, IARC re-affirmed this classification. There has been no causal link between carbon black exposure and cancer risk in humans. Applying the rules of the Globally Harmonized System of Classification and Labelling (GHS, e.g. UN 'Purple Book', EU CLP Regulation) the results of repeated dose toxicity and carcinogenicity studies in animals do not lead to classification of Carbon Black for Specific Target Organ Toxicity (Repeated exposure) and carcinogenicity. UN GHS says, that even if adverse effects are seen in animal studies or in-vitro tests, no classification is needed if the mechanism or mode of action is not relevant to humans. The European CLP Regulation also mentions, that no classification is indicated if the mechanism is not relevant to humans. Furthermore, the CLP guidance on classification and labelling states, that "lung overload" in animals is listed under mechanism not relevant to humans.

### GHS-Labeling

#### **Emergency Overview**

##### **Not classified**

The product contains no substances which at their given concentration, are considered to be hazardous to health

**Appearance:** Pellets

**Physical State:** Solid

**Odor:** None or slight

#### **Hazards not otherwise classified (HNOC)**

Not applicable

#### **Other Information**

Not applicable

Other hazards which do not result in classification:

#### **SABIC Emergency Overview**

- Pellets with slight or no odor
- Spilled material may create slipping hazard
- Can burn in a fire creating dense, toxic smoke
- Molten plastic can cause severe thermal burns
- Fumes produced during melt processing may cause eye, skin, and respiratory tract irritation. Severe over-exposure may result in nausea, headache, chills, and fever. See below for additional effects.
- Secondary operations, such as grinding, sanding, or sawing can produce dust which may present an explosion or respiratory hazard.



|                                       |                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
|---------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Other Information:</b>             | OSHA, IARC and/or NTP have listed carbon, titanium dioxide, crystalline silica (quartz), respirable glass and certain heavy metals, present in some colorants and fillers, as carcinogens. If these materials are present in this product at significant quantities, they are shown in Section 2/3. These materials are essentially bound to the plastic matrix and are unlikely to contribute to workplace exposure under recommended processing conditions. |
| <b>Processing Issues:</b>             | Processing vapors may cause irritation to the eyes, skin, and respiratory tract. In cases of severe exposure, nausea and headache can also occur. Grease-like processing vapor condensates on ventilation ductwork, molds, and other surfaces can cause irritation and injury to skin.                                                                                                                                                                        |
| <b>Aggravated Medical Conditions:</b> | MEDICAL RESTRICTIONS: There are no known health effects aggravated by exposure to this product. However, certain sensitive individuals and individuals with respiratory impairments may be affected by exposure to components in the processing vapors.                                                                                                                                                                                                       |

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Product Type Mixture

#### HAZARDOUS COMPONENTS:

| Chemical Name | CAS Number | Weight %   | GHS Classification (EC) No. 1272/2008 [CLP]: |
|---------------|------------|------------|----------------------------------------------|
| Carbon black  | 1333-86-4  | 0.3 - <1.0 |                                              |

For the full text of the H-statements, if mentioned in this section, see Section 16.

The non-hazardous components and exact percentage (concentration) of the composition have been withheld as a trade secret.

This product consists primarily of high molecular weight polymers which are not expected to be hazardous. The ingredients in this product are present within the polymer matrix and are not expected to be hazardous.

### 4. FIRST AID MEASURES

|                              |                                                                                                                                                                                                            |
|------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>If Inhalation:</b>        | Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. If symptoms persist, call a physician.                                                                         |
| <b>On skin contact:</b>      | Immediately cool the skin by rinsing with cold water after contact with hot material. Wash off immediately with soap and plenty of water. Consult a physician.                                             |
| <b>On contact with eyes:</b> | Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. If eye irritation persists, consult a specialist.                 |
| <b>On ingestion:</b>         | No hazards which require special first aid measures.                                                                                                                                                       |
| <b>Precautions:</b>          | Processing vapors inhalation may be irritating to the respiratory tract. If symptoms are experienced remove victim from the source of contamination or move victim to fresh air and obtain medical advice. |

## 5. FIRE-FIGHTING MEASURES

|                                                           |                                                                                                                                                                                                                                                                                     |
|-----------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Autoignition Temperature:</b>                          | No information available                                                                                                                                                                                                                                                            |
| <b>Explosive Properties:</b>                              | Avoid generating and accumulating dusts; fine dust dispersed in air in sufficient concentrations, and in the presence of an ignition source is a potential dust explosion hazard.                                                                                                   |
| <b>Suitable Extinguishing Media:</b>                      | Use dry chemical, CO <sub>2</sub> , water spray or "alcohol" foam. Water is the best extinguishing medium. Carbon dioxide and dry chemical are not generally recommended because their lack of cooling capacity may permit re-ignition on larger resin fires (blobs, drools, etc.). |
| <b>Unsuitable Extinguishing Media for Safety Reasons:</b> | Do not use a solid water stream as it may scatter and spread fire.                                                                                                                                                                                                                  |
| <b>Hazards from Combustion Products:</b>                  | Fire will produce dense black smoke containing hazardous combustion products, carbon oxides, hydrocarbon fragments, hydrogen cyanide, nitrogen oxides.                                                                                                                              |
| <b>Special Protective Equipment for Firefighters:</b>     | Do not enter fire area without proper protection including self-contained breathing apparatus and full protective equipment. Fight fire from a safe distance and a protected location due to the potential of hazardous vapors and decomposition products.                          |
| <b>Specific Hazards:</b>                                  | Take precautionary measures against static discharges. During processing, dust may form explosive mixture in air. Thermal decomposition can lead to release of irritating gases and vapors.                                                                                         |

## 6. ACCIDENTAL RELEASE MEASURES

|                                   |                                                                                                                             |
|-----------------------------------|-----------------------------------------------------------------------------------------------------------------------------|
| <b>Clean up:</b>                  | Sweep up and shovel into suitable containers for disposal. Do not create a powder cloud by using a brush or compressed air. |
| <b>Personal Precautions:</b>      | See section 8.                                                                                                              |
| <b>Environmental Precautions:</b> | Do not flush into surface water or sanitary sewer system. Material should not be released into the environment.             |

## 7. HANDLING AND STORAGE

|                               |                                                                                                                                                                                                                                                     |
|-------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Handling:</b>              | Handle in accordance with good industrial hygiene and safety practices. Provide for appropriate exhaust ventilation and dust collection at machinery. Avoid dust formation. All metal parts of the mixing and processing equipment must be earthed. |
| <b>Storage:</b>               | Store in closed container in a dry and cool area. Keep away from heat sources and sources of ignition. Keep away from food, drink and animal feeding stuffs. Keep container tightly closed in a dry and well-ventilated place.                      |
| <b>Incompatible Products:</b> | Strong acids, strong oxidizing agents.                                                                                                                                                                                                              |

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

### Exposure limits:

No components with information, unless noted below

| Chemical Name             | US OSHA PEL<br>(8 Hr)                                             | ACGIH                                                                                   | Canada - Alberta<br>(8 Hr)      | Mexico OEL Data                                                                 | SABIC Recommend<br>(8 Hr)* |
|---------------------------|-------------------------------------------------------------------|-----------------------------------------------------------------------------------------|---------------------------------|---------------------------------------------------------------------------------|----------------------------|
| Carbon black<br>1333-86-4 | FRL_TWA: 3.5 mg/m <sup>3</sup><br>; TL_PEL: 3.5 mg/m <sup>3</sup> | TWA: 3.5 mg/m <sup>3</sup> ;<br>Notations: Not<br>Classifiable as a<br>Human Carcinogen | OEL_8 hr: 3.5 mg/m <sup>3</sup> | LMPE-PPT: 3.5 mg/m <sup>3</sup><br>; LMPE-CT: 7 mg/m <sup>3</sup> ;<br>CONN: A4 | No Information             |

\*SABIC Recommended Exposure Limits have been established for certain chemicals.

### Engineering Measures to Reduce Exposure:

Handle in accordance with good industrial hygiene and safety practices. Provide for appropriate exhaust ventilation at machinery. Processing fume condensate may be a fire hazard and toxic; remove periodically from exhaust hoods, ductwork, and other surfaces using appropriate personal protection.

### Hand Protection:

Protective gloves should be worn.

### Eye Protection:

Safety glasses with side-shields or chemical goggles. In addition, use full-face shield when cleaning processing vapor condensates from hood, ducts, and other surfaces.

### Respiratory Protection:

When using this product at elevated temperatures, implement engineering systems, administrative controls or a respiratory protection program (including a respirator approved for protection from organic vapors, acid, gases, and particulate matter) if processing vapors are not adequately controlled or operators experience symptoms of overexposure. If dust or powder are produced from secondary operations such as sawing or grinding, use a respirator approved for protection from dust.

### Body Protection:

Long sleeved clothing.

### Hygiene Measures:

When using, do not eat, drink or smoke.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

|                                             |                                                                                                              |
|---------------------------------------------|--------------------------------------------------------------------------------------------------------------|
| Physical State:                             | Solid                                                                                                        |
| Appearance:                                 | Pellets                                                                                                      |
| Color:                                      | Same as color code                                                                                           |
| Odor:                                       | None or slight                                                                                               |
| Odor Threshold:                             | No information available                                                                                     |
| pH                                          | No data available                                                                                            |
| Boiling point/range:                        | Not determined                                                                                               |
| Melting point/range:                        | This product does not exhibit a sharp melting point but softens gradually over a wide range of temperatures. |
| Autoignition Temperature:                   | No information available                                                                                     |
| Flammability (solid, gas):                  | No information available                                                                                     |
| Vapor Pressure:                             | Negligible                                                                                                   |
| Water Solubility:                           | Insoluble                                                                                                    |
| Partition coefficient:<br>(n-octanol/water) | No information available                                                                                     |
| Vapor Density:                              | Not determined                                                                                               |
| Evaporation Rate:                           | Negligible                                                                                                   |
| Decomposition temp. (°C) :                  | Not determined                                                                                               |
| Specific gravity:                           | >1; (water = 1)                                                                                              |
| VOC content (%):                            | Negligible                                                                                                   |
| Explosive Limits                            |                                                                                                              |
| upper:                                      | Not determined                                                                                               |
| lower:                                      | Not determined                                                                                               |

## 10. STABILITY AND REACTIVITY

|                                   |                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
|-----------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Stability:                        | Stable under ambient conditions. Hazardous polymerization does not occur.                                                                                                                                                                                                                                                                                                                                                                                              |
| Conditions to Avoid:              | To avoid thermal decomposition, avoid elevated temperatures. Heating can result in the formation of gaseous decomposition products, some of which may be hazardous. Do not exceed melt temperature recommendations in product literature. Purgings of hot material should be collected in small, flat, thin shapes and quenched with water to allow for rapid cooling. Do not allow product to remain in barrel at elevated temperatures for extended periods of time. |
| Hazardous Decomposition Products: | Process vapors under recommended processing conditions may include trace levels of hydrocarbons, styrene, acrylonitrile, acrolein, acetaldehyde, acetophenone, ethyl benzene, cumene, alpha methylstyrene, 4-vinylcyclohexene, phenols.                                                                                                                                                                                                                                |
| Incompatible Products:            | Strong acids, strong oxidizing agents.                                                                                                                                                                                                                                                                                                                                                                                                                                 |

## 11. TOXICOLOGICAL INFORMATION

### Acute Toxicity

|                             |                                                                                   |
|-----------------------------|-----------------------------------------------------------------------------------|
| <b>LD50/oral/rat:</b>       | >5000 mg/kg (estimated)                                                           |
| <b>LD50/dermal/rabbit:</b>  | >2000 mg/kg estimated                                                             |
| <b>Inhalation:</b>          | Pellet inhalation unlikely due to physical form.                                  |
| <b>Eye Contact:</b>         | Resin particles, like other inert materials, are mechanically irritating to eyes. |
| <b>Skin Contact:</b>        | Not a hazard with pellets during normal industrial use.                           |
| <b>Ingestion:</b>           | Pellet ingestion unlikely due to physical form.                                   |
| <b>Chronic Toxicity:</b>    | No information available.                                                         |
| <b>Subchronic Toxicity:</b> | No information available                                                          |
| <b>Primary Irritation:</b>  | Substance does not generally irritate and is only mildly irritating to the skin.  |
| <b>IARC:</b>                | Not listed                                                                        |
| <b>OSHA:</b>                | Not regulated                                                                     |
| <b>NTP:</b>                 | Not tested                                                                        |
| <b>Remarks:</b>             | The toxicological data has been taken from products of similar composition.       |

### Special Studies:

**Styrene:** A reproduction study in rats exposed to 125 and 250 ppm in drinking water (approximately 14-21 mg/kg/day) produced no treatment-related effects on reproductive performance over 3-generations. The only treatment related findings were reduced pup survival index in the F1 and F2 offspring. There was no evidence of developmental effects and no other effects were reported. The parental NOEL was 250 ppm and the NOEL for the F1 and F2 offspring was 125 ppm. In developmental toxicity studies in rats, rabbits, and hamsters styrene was not a selective toxicant to the fetus and was toxic at only those doses that produced maternal toxicity.

In humans, styrene is associated with central nervous system depression (headache, fatigue, nausea, and dizziness) at inhalation concentrations greater than 50 ppm. Styrene has also been reported to reduce sensory nerve conduction in occupation settings after exposure to 100 ppm or more. Styrene has also been reported to produce color vision deficiencies (dyschromatopsia) at concentrations greater than 8 ppm (averaging 24 ppm). Twelve epidemiology studies have been reported for styrene and half have supported the hypothesis that styrene produces lymphatic and hematopoietic cancers (LHC). However, those that show an increase of LHC has generally been small in size (limited statistical power), have shown no dose-response relationship, and/or had multiple chemical exposures. Of the six studies that have not shown an association with styrene and LHC, these studies tended to be larger in size (higher statistical power), had an older study population, and had good exposure data. Overall, the weight of evidence suggests that there is not an association of LHC and styrene exposure in humans.

In a recent inhalation cancer bioassay, Sprague Dawley derived rats (70/sex/group) were exposed whole body to styrene vapor at 0, 50, 200, 500, or 1000 ppm 6 h/day 5 days/week for 104 weeks. Males exposed to 500 and 1000 ppm and females exposed to 200 ppm and higher gained significantly less weight than the controls. There were no changes of toxicologic significance in hematology, clinical chemistry, urinalysis, or organ weights. Styrene-related non-neoplastic histopathologic changes were confined to the olfactory epithelium of the nasal mucosa. The incidence and severity were related to dose. There was no evidence that styrene exposure caused treatment related increases of any tumor type in males or females or in the number of tumor bearing rats in the exposed groups compared to controls. In 2-year carcinogenicity bioassays conducted by the National Toxicology Program, rats and mice (50/sex/group) received 0, 500, 1000, or 2000 mg/kg/day and 0, 150, or 300 mg/kg/day, respectively, via oral gavage. In male or female rats and female mice there was no significant difference in tumor incidence when compared to the control groups. In male mice there was a positive association between styrene dose and the incidence of the combination of adenomas and carcinomas of the lung. However, due to the high background incidence of this tumor type in male mice, no firm conclusion was drawn for the carcinogenicity. In a study that administered styrene (125 and 250 ppm) in the drinking water of rats for 2 years, there was no evidence of carcinogenicity. In other chronic inhalation toxicity studies, rats were exposed to styrene via inhalation at concentrations up to 300 ppm for 4-6 hours/day, 5 days/week, for 1 year or up to 1000 ppm for 2 years. There was a slightly increased, but not statistically significant, incidence of mammary tumors in the females in both studies. Because the control incidence was also high and there was no dose-response relationship the studies were considered to be negative.

**Carbon Black:** The International Agency for Research on Cancer (IARC) has determined that carbon black is a class 2B known animal and possible human carcinogen by the route of inhalation. Rats exposed to high doses of carbon black by inhalation developed statistically significant increases in lung fibrosis and lung tumors.

**Carbon Black:** The scientific discussions about the carcinogenic potential of inorganic low solubility particles (fine dust) including carbon black has not been concluded. Many inhalation toxicologists believe the lung fibrosis and tumors that developed in rats following exposure to carbon black result from massive accumulation of small dust particles that overwhelm the clearance mechanism and produce what is termed "lung overload," an effect considered to be rat specific and not relevant to humans. In addition, based on epidemiological studies, no causal link between carbon black exposure and cancer risk in humans has been demonstrated.



## 12. ECOLOGICAL INFORMATION

|                             |                                                                |
|-----------------------------|----------------------------------------------------------------|
| <b>Ecotoxicity Effects:</b> | Do not flush into surface water or sanitary sewer system.      |
| <b>Other information:</b>   | Ecological damages are not known or expected under normal use. |

## 13. DISPOSAL CONSIDERATIONS

|                                               |                                                                                                                                                                                                                         |
|-----------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Waste from residues / unused products:</b> | Where possible recycling is preferred to disposal or incineration. Descartar em conformidade com as legislação locais.                                                                                                  |
| <b>Contaminated Packaging:</b>                | Empty containers should be transported/delivered using a registered waste carrier for local recycling or waste disposal.                                                                                                |
| <b>Waste Disposal:</b>                        | Recycling is encouraged. Landfill or incinerate in accordance with federal, state and local requirements. Collected processing fume condensates and incinerator ash should be tested to determine waste classification. |

## 14. TRANSPORT INFORMATION

|                                  |                                                                                                       |
|----------------------------------|-------------------------------------------------------------------------------------------------------|
| <b>Transport Classification:</b> | Not regulated as hazardous for shipment, unless noted below, under current transportation guidelines. |
|----------------------------------|-------------------------------------------------------------------------------------------------------|

DOT

ADR/RID/ADN

IMDG

ICAO

IATA-DGR

MEXICO

CANADA/TDG

## 15. REGULATORY INFORMATION

### International Inventories:

|                                |                                                    |
|--------------------------------|----------------------------------------------------|
| <b>TSCA (USA):</b>             | Listed                                             |
| <b>DSL (Canada):</b>           | Not listed - One or more components listed on NDSL |
| <b>EINECS/ELINCS (Europe):</b> | Listed                                             |
| <b>ENCS (Japan):</b>           | Listed                                             |
| <b>IECSC (China):</b>          | Listed                                             |
| <b>KECL (Korea):</b>           | Listed                                             |
| <b>PICCS (Philippines):</b>    | Listed                                             |
| <b>AICS (Australia):</b>       | Listed                                             |
| <b>NZIoC (New Zealand):</b>    | Listed                                             |

**Other Inventory Information:**

A "Listed" entry above means all chemical components are on the respective inventory list and/or a qualifying exemption exists for one or more components. A "Not listed" entry above indicates one or more components is restricted from import or manufacture into that country/region. Articles are exempt from registration and are therefore not listed on the national chemical inventories.

**SVHC (REACH Regulation (EC) No 1907/2006 and 453/2010, as amended):**

This product does not intentionally contain SVHC chemicals except as noted below. Incidental amounts of impurities, if present, would be below the threshold limit of 0.1% by weight.

**SARA (313) Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA):**

This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

**SARA (311, 312) hazard class:**

|                                   |   |
|-----------------------------------|---|
| Acute Health Hazard               | N |
| Chronic Health Hazard             | N |
| Fire Hazard                       | N |
| Sudden Release of Pressure Hazard | N |
| Reactive Hazard                   | N |

**Canada - WHMIS Classification:**

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all the information required by the CPR. Unless noted below, this product is non-controlled. Some classifications may not apply to the entire product.

**California Proposition 65:**

Components in this product known to the State of California to cause cancer and/or reproductive effects, are listed below:

| Chemical Name                                        | Weight %   | California Proposition 65:                                                               |
|------------------------------------------------------|------------|------------------------------------------------------------------------------------------|
| Carbon black<br>1333-86-4                            | 0.3 - <1.0 | Listed: February 21, 2003 Carcinogenic. (airborne, unbound particles of respirable size) |
| 4,4'-isopropylidenediphenol (bisphenol A)<br>80-05-7 | ≤100 ppm   | Listed: May 11, 2015 Type of Toxicity: Female                                            |
| Acrylonitrile<br>107-13-1                            | ≤100 ppm   | Type of Toxicity: cancer                                                                 |
| Cumene<br>98-82-8                                    | ≤100 ppm   | Type of Toxicity: cancer                                                                 |
| Ethylbenzene<br>100-41-4                             | ≤100 ppm   | Type of Toxicity: cancer                                                                 |
| Methylene chloride<br>75-09-2                        | ≤10 ppm    | Type of Toxicity: cancer                                                                 |
| Butadiene<br>106-99-0                                | ≤10 ppm    | Type of Toxicity: cancer ; Type of Reproductive Toxicity: developmental, female, male    |

**RoHS EU Directive 2011/65/EU:**

The subject product is in compliance with EU RoHS Directive 2011/65/EU. All below chemicals are not employed in the manufacture of the product: a.Cadmium and its compounds, b.Lead and its compounds, c.Mercury and its compounds, d.Hexavalent chromium compounds, e.Polybrominated biphenyls (PBBs), f.Polybrominated diphenyl ethers (PBDEs including Deca-BDE). The trace levels of heavy metals may be present as impurities within threshold limits (<0.1% for Pb, Hg, Cr VI, and <0.01% for Cd). We are disclosing this information, to the best of our knowledge, based upon data from our raw material manufacturers.

**HMIS Rating**

Health: 0

Flammability: 1

Reactivity: 0

## 16. OTHER INFORMATION

**SABIC and brands marked with <sup>TM</sup> are trademarks of SABIC or its subsidiaries or affiliates.**

Visit our public website to search, view and print Safety Data Sheets for commercial products:

<http://eur.sabic-ip.com/ordeur/pages/msds/MSDSSearch.jsp?app=sabic-ip>

**SDS Scope:**

USA: Conforms to 29 CFR 1910.1200 (2012 OSHA Hazard Communication Standard)

This document is also applicable in other countries and regions.

**Prepared by:** Product Stewardship & Toxicology

**Reason for revision:** Update to GHS format

DISCLAIMER: This Safety Data Sheet [SDS] information is provided based on the Hazard Communication Regulations for your region or country and for the use of the persons required to receive this information under those regulations. The information is neither designed nor recommended for any other use or for use by any other person, including for compliance with other laws. SABIC Innovative Plastics does not warrant the suitability for use of this SDS for any other material or product not specifically identified herein. SABIC Innovative Plastics does not warrant the accuracy or authenticity of this SDS unless it has been obtained directly from SABIC Innovative Plastics, or posted or viewed on a SABIC Innovative Plastics website. Modification of this SDS, unless specifically authorized by SABIC Innovative Plastics, is strictly prohibited. This SDS is based on information that is believed to be reliable, but may be subject to change as new information becomes available. Because it is not possible to anticipate all conditions of use, additional safety precautions may be required. Since the use of this material is not under SABIC Innovative Plastics' control, each user is responsible for making its own determination as to the safe and proper handling of this material in its own particular use of this material. SABIC INNOVATIVE PLASTICS MAKES NO REPRESENTATION OR WARRANTY, EITHER EXPRESS OR IMPLIED, INCLUDING AS TO MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Each user should read and understand this information and incorporate it into individual site safety programs as required by applicable hazard communication standards and regulations.

**End of Safety Data Sheet**