

SAFETY DATA SHEET According to Regulation (EC) No 1907/2006 and 453/2010 (REACH)

Print date: 12-May-2015 Revision Number: 2 Revision date: 05-May-2015

1. IDENTIFICATION OF THE SUBSTANCE AND COMPANY

Trademark: LUBRICOMP™ Product Code: ML008 - NC

Product Description: Polypropylene [CASRN 9003-07-0]

Product Type: Commercial Product

Restrictions on Use: Contains Industry recycled material

Recommended use: May be used to produce molded or extruded articles or as a component of other industrial

products.

Company: SABIC Innovative Plastics B.V.

Plasticslaan 1 P.O. Box 117

4600 AC Bergen op Zoom

The Netherlands

Manufacturer: SABIC Innovative Plastics

Ottergeerde 22-28

4941 VM Raamsdonksveer

The Netherlands

Emergency Telephone Number

(United States):

Bergen op Zoom +31(0)164-292911 (24/24)

Emergency 800 424-9300 (USA)

Transportation/CHEMTREC

(24 HOUR):

+1 703-527-3887 (globally, outside USA)

E-mail: webinquiries@sabic-ip.com

Website Address: www.sabic-ip.com

2. HAZARDS IDENTIFICATION

The additives in this product are bound in a thermoplastic resin matrix. In accordance with GHS for the classification of the product, the hazard potential may be assessed with respect to the physico-chemical form and/or bioavailability of the individual components in the thermoplastic resin.

Where GHS classifications are shown below, these are based on the individual components in the thermoplastic resin matrix. Under the typical use conditions for the resin, these hazardous components are unlikely to contribute to workplace exposure. Please read the entire safety data sheet and/or consult an EHS professional for a complete understanding.

Classification of the substance or mixture

REGULATION (EC) No 1272/2008

Not hazardous Not classified

Classification according to EU Directives 67/548/EEC or 1999/45/EC

Product Name: ML-4080 NAT Page 1 of 8 Revision date: 05-May-2015



CLP/GHS-Labeling

GHS Labeling not required

Precautionary Statements

No GHS specific Precautionary Statements required - observe all other warnings and handling instructions in this SDS.

Other hazards which do not result in classification:

SABIC Emergency Overview

- · Pellets with slight or no odor
- · Spilled material may create slipping hazard
- · Can burn in a fire creating dense, toxic smoke
- Molten plastic can cause severe thermal burns
- Fumes produced during melt processing may cause eye, skin, and respiratory tract irritation. Severe over-exposure may result in nausea, headache, chills, and fever. See below for additional effects.
- Secondary operations, such as grinding, sanding, or sawing can produce dust which may present an explosion or respiratory hazard.

Other Information: Cool skin rapidly with cold water after contact with molten material. Heating can release

hazardous gases. Hazardous fumes can also occur in post-processing operations.

Processing Issues: Processing vapors may cause irritation to the eyes, skin, and respiratory tract. In cases of

severe exposure, nausea and headache can also occur. Grease-like processing vapor condensates on ventilation ductwork, molds, and other surfaces can cause irritation and

injury to skin.

Aggravated Medical Conditions: MEDICAL RESTRICTIONS: There are no known health effects aggravated by exposure to

this product. However, certain sensitive individuals and individuals with respiratory impairments may be affected by exposure to components in the processing vapors.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Product Type Mixture

For the full text of the H-phrases, if mentioned in this section, see Section 16.

The non-hazardous components and exact percentage (concentration) of the composition have been withheld as a trade secret.

This product consists primarily of high molecular weight polymers which are not expected to be hazardous. The ingredients in this product are present within the polymer matrix and are not expected to be hazardous.

Product Name: ML-4080 NAT Page 2 of 8 Revision date: 05-May-2015



4. FIRST AID MEASURES

If Inhalation: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion

If symptoms persist, call a physician

Immediately cool the skin by rinsing with cold water after contact with hot material Wash off On skin contact:

immediately with soap and plenty of water Consult a physician

On contact with eyes: Immediately flush with plenty of water. After initial flushing, remove any contact lenses and

continue flushing for at least 15 minutes If eye irritation persists, consult a specialist

On ingestion: No hazards which require special first aid measures

Cool molten product on skin with plenty of water. Do not remove solidified product Do not **Precautions:**

peel polymer from the skin

5. FIRE-FIGHTING MEASURES

Autoignition Temperature: No information available

Explosive Limits

upper: Not determined

Not determined lower:

Suitable Extinguishing Media: Water spray mist or foam Use dry chemical, CO2, water spray or "alcohol" foam. Water is

> the best extinguishing medium. Carbon dioxide and dry chemical are not generally recommended because their lack of cooling capacity may permit re-ignition on larger resin

fires (blobs, drools, etc.)

for Safety Reasons:

Unsuitable Extinguishing Media Carbon dioxide and dry chemical are not recommended because their lack of cooling

capacity may permit re-ignition Do not use a solid water stream as it may scatter and

spread fire

Hazardous Decomposition

Products:

Fire will produce dense black smoke containing hazardous combustion products carbon oxides hydrocarbons fragments hydrogen fluoride carbonyl fluoride fluorocarbons See

section 10

Special Protective Equipment

for Firefighters:

In the event of fire, wear self-contained breathing apparatus (EU: NEN-EN137)

Specific Hazards: Take precautionary measures against static discharges During processing, dust may form

explosive mixture in air Thermal decomposition can lead to release of irritating gases and

vapors

Product Name: ML-4080 NAT Page 3 of 8 Revision date: 05-May-2015



6. ACCIDENTAL RELEASE MEASURES

Sweep up and shovel into suitable containers for disposal. Do not create a powder cloud by

using a brush or compressed air.

Personal Precautions: See section 8.

Environmental Precautions: Do not flush into surface water or sanitary sewer system. Material should not be released

into the environment.

7. HANDLING AND STORAGE

Handling: Handle in accordance with good industrial hygiene and safety practices. Provide for

appropriate exhaust ventilation and dust collection at machinery. Avoid dust formation. All

metal parts of the mixing and processing equipment must be earthed.

Storage: Store in closed container in a dry and cool area. Keep away from heat sources and sources

of ignition.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure limits: No components with information, unless noted below

*SABIC Recommended Exposure Limits have been established for certain chemicals.

Engineering Measures

toExposure:

Clean up:

In the case of hazardous fumes, wear self-contained breathing apparatus. Wear face-shield and protective suit for abnormal processing problems. Handle in accordance with good

industrial hygiene and safety practice. Provide for appropriate exhaust ventilation at

machinery.

Hand Protection: Protective gloves should be worn. (EU: NEN-EN 374).

Eye Protection: Safety glasses with side-shields. (EU: NEN-EN 165-166).

Respiratory Protection: In the case of hazardous fumes, wear self contained breathing apparatus. In case of

insufficient ventilation wear suitable respiratory equipment. (EU: NEN-EN149).

Body Protection: Long sleeved clothing. (EU: NEN-EN 340-369-465).

Hygiene Measures: When using, do not eat, drink or smoke.

Product Name: ML-4080 NAT Page 4 of 8 Revision date: 05-May-2015



9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State:SolidAppearance:Pellets

Color: Varies Same as color code

Odor: None

Melting point/range: Various

Autoignition Temperature: No information available

Vapor Pressure: Negligible

Water Solubility: Insoluble Evaporation Rate: Negligible

Specific gravity: >1; (water = 1)
VOC content (%): Negligible

Explosive Limits

upper: Not determined lower: Not determined

10. STABILITY AND REACTIVITY

Stability: Stable under ambient conditions. Hazardous polymerization does not occur.

Conditions to Avoid: To avoid thermal decomposition, avoid elevated temperatures. Heating can result in the

formation of gaseous decomposition products, some of which may be hazardous. Do not exceed melt temperature recommendations in product literature. Purgings of hot material should be collected in small, flat, thin shapes and quenched with water to allow for rapid cooling. Do not allow product to remain in barrel at elevated temperatures for extended

periods of time.

Hazardous Decomposition

Products:

Traces of, phenols, alkylphenols, diarylcarbonates, carbonyl fluoride, hydrogen fluoride, fluorocarbons, perfluorohydrocarbon fragments, carbon oxides, aldehydes, alcohols,

organic acids.

11. TOXICOLOGICAL INFORMATION

LD50/oral/rat: >5000 mg/kg

LD50/dermal/rabbit: >2000 mg/kg

Subchronic Toxicity: No information available

Primary Irritation: Substance does not generally irritate and is only mildly irritating to the skin

Remarks: The toxicological data has been taken from products of similar composition

Special Studies: Thermal degradation of the fluoropolymer additives in this product may result in the release

of pyrolysis products and fumes. Short term inhalation exposure may cause influenza-like symptoms such as chest pain/tightness, shortness of breath, sore throat, fever and chills, malaise and sometimes headache (also known as "polymer fume fever"). Following removal from exposure, complete resolution is expected within 12-48 hours. Prolonged and repeated exposure to high levels may lead to effects such as pulmonary edema and lung

disease.

Product Name: ML-4080 NAT Page 5 of 8 Revision date: 05-May-2015



12. ECOLOGICAL INFORMATION

Ecotoxicity Effects: Do not flush into surface water or sanitary sewer system.

Ecotoxicity - Invertebrate Data: Ecological damages are not known or expected under normal use.

Germany VCI (WGK): 0

13. DISPOSAL CONSIDERATIONS

Waste from residues / unused

products:

Where possible recycling is preferred to disposal or incineration. Dispose of in accordance

with local regulations.

Contaminated Packaging: Empty containers should be transported/delivered using a registered waste carrier for local

recycling or waste disposal.

EWC waste disposal no: 702 - waste from the manufacture, formulation, supply and use of plastics, synthetic rubber

and man-made fibres.

14. TRANSPORT INFORMATION

Transport Classification: Not regulated as hazardous for shipment, unless noted below, under current transportation

guidelines.

DOT

ADR/RID/ADN

IMDG

ICAO

IATA-DGR

Product Name: ML-4080 NAT Page 6 of 8 Revision date: 05-May-2015



15. REGULATORY INFORMATION

This substance is classified and labelled according to Annex I of Directive 67/548/EEC, as amended.

International Inventories:

TSCA (USA): Listed DSL (Canada): Listed **EINECS/ELINCS (Europe):** Listed ENCS (Japan): Listed IECSC (China): Listed **KECL** (Korea): Listed PICCS (Philippines): Listed AICS (Australia): Listed NZIoC (New Zealand): Listed

REACH Information: For this product's REACH related information, please contact webinquiries@sabic-ip.com

Other Inventory Information:

A "Listed" entry above means all chemical components are on the respective inventory list and/or a qualifying exemption exists for one or more components. A "Not listed" entry above indicates one or more components is restricted from import or manufacture into that country/region. Articles are exempt from registration and are therefore not listed on the national chemical inventories.

SVHC (REACH Regulation (EC) No 1907/2006 and 453/2010, as amended):

This product does not intentionally contain SVHC chemicals except as noted below. Incidental amounts of impurities, if present, would be below the threshold limit of 0.1% by weight.

California Proposition 65:

This product does not contain components known to the State of California to cause cancer and/or reproductive effects.

The product does not contain compensation to the class of camerina to cause			the Ctate of Camerina to Cauco Carrott analysis represents the Constitution
	Chemical Name	Weight %	California Proposition 65:
	Polypropylene	30-70	
	9003-07-0		

RoHS EU Directive 2011/65/EU:

The subject product is in compliance with EU RoHS Directive 2011/65/EU. All below chemicals are not employed in the manufacture of the product: a.Cadmium and its compounds, b.Lead and its compounds, c.Mercury and its compounds, d.Hexavalent chromium compounds, e.Polybrominated biphenyls (PBBs), f.Polybrominated diphenyl ethers (PBDEs including Deca-BDE). The trace levels of heavy metals may be present as impurities within threshold limits (<0.1% for Pb, Hg, Cr VI, and <0.01% for Cd). We are disclosing this information, to the best of our knowledge, based upon data from our raw material manufacturers.

16. OTHER INFORMATION

SABIC and brands marked with ™ are trademarks of SABIC or its subsidiaries or affiliates.

Visit our public website to search, view and print Safety Data Sheets for commercial products: http://eur.sabic-ip.com/ordeur/pages/msds/MSDSSearch.jsp?app=sabic-ip

SDS Scope:

Europe: Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Regulation (EU) No. 453/2010. This document is also applicable in other countries and regions.

Prepared by: Product Stewardship & Toxicology

Product Name: ML-4080 NAT Page 7 of 8 Revision date: 05-May-2015



DISCLAIMER: This Safety Data Sheet [SDS] information is provided based on the Hazard Communication Regulations for your region or country and for the use of the persons required to receive this information under those regulations. The information is neither designed nor recommended for any other use or for use by any other person, including for compliance with other laws. SABIC Innovative Plastics does not warrant the suitability for use of this SDS for any other material or product not specifically identified herein. SABIC Innovative Plastics does not warrant the accuracy or authenticity of this SDS unless it has been obtained directly from SABIC Innovative Plastics, or posted or viewed on a SABIC Innovative Plastics website. Modification of this SDS, unless specifically authorized by SABIC Innovative Plastics, is strictly prohibited. This SDS is based on information that is believed to be reliable, but may be subject to change as new information becomes available. Because it is not possible to anticipate all conditions of use, additional safety precautions may be required. Since the use of this material is not under SABIC Innovative Plastics' control, each user is responsible for making its own determination as to the safe and proper handling of this material in its own particular use of this material. SABIC INNOVATIVE PLASTICS MAKES NO REPRESENTATION OR WARRANTY, EITHER EXPRESS OR IMPLIED, INCLUDING AS TO MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Each user should read and understand this information and incorporate it into individual site safety programs as required by applicable hazard communication standards and regulations.

End of Safety Data Sheet

Product Name: ML-4080 NAT Page 8 of 8 Revision date: 05-May-2015