

SAFETY DATA SHEET According to Regulation (EC) No 1907/2006 and 453/2010 (REACH)

Print date: 29-May-2015 Revision Number: 2 Revision date: 28-May-2015

1. IDENTIFICATION OF THE SUBSTANCE AND COMPANY

Website Address:	www.sabic.com
E-mail:	sds.info@sabic.com
Emergency Telephone Number:	SITTARD +31 (0)46 476 55 55 (0h - 24h)
Manufacturer:	SABIC Polymers Genk, Belgium Geleen, The Netherlands Wilton, United Kingdom and/or Gelsenkirchen, Germany
Company:	SABIC SALES Europe B.V. or any of its Affiliates Europaboulevard 1, 6135 LD SITTARD P.O. Box 5151, 6130 PD SITTARD The Netherlands
Recommended use:	May be used to produce molded or extruded articles or as a component of other industrial products.
Product Type:	Commercial Product
Product Description:	Poly (propylene-ethylene) [CASRN 9010-79-1]
Product Name:	QR674K - 00900

Product Name: QR674K-00900 Page 1 of 8 Revision date: 28-May-2015



2. HAZARDS IDENTIFICATION

The additives in this product (if any) are bound in a thermoplastic resin matrix. In accordance with GHS for the classification of the product, the hazard potential may be assessed with respect to the physico-chemical form and/or bioavailability of the individual components in the thermoplastic resin.

Where GHS classifications are shown below, these are based on the individual components in the thermoplastic resin matrix. Under the typical use conditions for the resin, these hazardous components are unlikely to contribute to workplace exposure. Please read the entire safety data sheet and/or consult an EHS professional for a complete understanding.

Classification of the substance or mixture

REGULATION (EC) No 1272/2008

Not hazardous

Not classified

Classification according to EU Directives 67/548/EEC or 1999/45/EC

CLP/GHS-Labeling

GHS Labeling not required

Precautionary Statements

No GHS specific Precautionary Statements required - observe all other warnings and handling instructions in this SDS.

Other hazards which do not result in classification:

SABIC Emergency Overview

· Pellets with slight or no odor

Processing Issues:

- Spilled material may create slipping hazard
- · Can burn in a fire creating dense, toxic smoke
- · Molten plastic can cause severe thermal burns
- Fumes produced during melt processing may cause eye, skin, and respiratory tract irritation. Severe over-exposure may result in nausea, headache, chills, and fever. See below for additional effects.
- Secondary operations, such as grinding, sanding, or sawing can produce dust which may present an explosion or respiratory hazard.

Other Information: Cool skin rapidly with cold water after contact with molten material. Heating can release

hazardous gases. Hazardous fumes can also occur in post-processing operations. Processing vapors may cause irritation to the eyes, skin, and respiratory tract. In cases of

severe exposure, nausea and headache can also occur. Grease-like processing vapor

severe exposure, nausea and neadache can also occur. Grease-like processing vapor condensates on ventilation ductwork, molds, and other surfaces can cause irritation and

injury to skin.

Aggravated Medical Conditions: MEDICAL RESTRICTIONS: There are no known health effects aggravated by exposure to

this product. However, certain sensitive individuals and individuals with respiratory impairments may be affected by exposure to components in the processing vapors.

Product Name: QR674K-00900 Page 2 of 8 Revision date: 28-May-2015



3. COMPOSITION/INFORMATION ON INGREDIENTS

Product Type

Mixture

For the full text of the H-phrases, if mentioned in this section, see Section 16.

The non-hazardous components and exact percentage (concentration) of the composition have been withheld as a trade secret.

This product consists primarily of high molecular weight polymers which are not expected to be hazardous. The ingredients in this product are present within the polymer matrix and are not expected to be hazardous.

4. FIRST AID MEASURES

If Inhalation: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion

If symptoms persist, call a physician

On skin contact: Immediately cool the skin by rinsing with cold water after contact with hot material Wash off

immediately with soap and plenty of water Consult a physician

On contact with eyes: Immediately flush with plenty of water. After initial flushing, remove any contact lenses and

continue flushing for at least 15 minutes If eye irritation persists, consult a specialist

On ingestion: No hazards which require special first aid measures

Precautions: Cool molten product on skin with plenty of water. Do not remove solidified product Do not

peel polymer from the skin

Product Name: QR674K-00900 Page 3 of 8 Revision date: 28-May-2015



5. FIRE-FIGHTING MEASURES

Autoignition Temperature:

>300°C

Explosive Limits

upper:

Not determined

lower:

Not determined

Suitable Extinguishing Media: Use dry chemical, CO2, water spray or "alcohol" foam. Water is the best extinguishing

> medium. Carbon dioxide and dry chemical are not generally recommended because their lack of cooling capacity may permit re-ignition on larger resin fires (blobs, drools, etc.)

for Safety Reasons:

Unsuitable Extinguishing Media Do not use a solid water stream as it may scatter and spread fire

Hazardous Decomposition

Products:

Fire will produce dense black smoke containing hazardous combustion products, carbon

oxides.

Hazards from Combustion

Products:

Fire will produce dense black smoke containing hazardous combustion products, carbon

oxides, hydrocarbon fragments,

Special Protective Equipment

for Firefighters:

In the event of fire, wear self-contained breathing apparatus (EU: NEN-EN137)

Take precautionary measures against static discharges During processing, dust may form **Specific Hazards:**

explosive mixture in air Thermal decomposition can lead to release of irritating gases and

vapors

6. ACCIDENTAL RELEASE MEASURES

Clean up: Sweep up and shovel into suitable containers for disposal. Do not create a powder cloud by

using a brush or compressed air.

Personal Precautions: See section 8. If spilled, take caution, as material can cause surfaces to become very

slippery.

Environmental Precautions: Do not flush into surface water or sanitary sewer system. Material should not be released

into the environment.

7. HANDLING AND STORAGE

Handling: Handle in accordance with good industrial hygiene and safety practices. Provide for

> appropriate exhaust ventilation and dust collection at machinery. Minimize dust generation and accumulation. Routine housekeeping should be instituted to ensure that dusts do not accumulate on surfaces. Dry powders can build static electricity charges when subjected to the friction of transfer and mixing operations. Provide adequate precautions, such as

electrical grounding and bonding, or inert atmospheres.

Storage: Store in a dry and cool area. Keep away from heat sources and sources of ignition. Keep

away from direct sunlight.

Product Name: QR674K-00900 Page 4 of 8 Revision date: 28-May-2015



8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure limits:

No components with information, unless noted below

*SABIC Recommended Exposure Limits have been established for certain chemicals.

Engineering Measures

toExposure:

In the case of hazardous fumes, wear self-contained breathing apparatus. Wear face-shield and protective suit for abnormal processing problems. Handle in accordance with good

industrial hygiene and safety practice. Provide for appropriate exhaust ventilation at

machinery.

Hand Protection: Protective gloves should be worn. (EU: NEN-EN 374). When handling hot material, wear

heat-resistant protective gloves that are able to withstand the temperature of molton resin.

Eye Protection: Safety glasses with side-shields. (EU: NEN-EN 165-166).

Respiratory Protection: In the case of hazardous fumes, wear self contained breathing apparatus. In case of

insufficient ventilation wear suitable respiratory equipment. (EU: NEN-EN149).

Body Protection: Long sleeved clothing. (EU: NEN-EN 340-369-465).

Hygiene Measures: When using, do not eat, drink or smoke.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State: Solid Appearance: Pellets

Color: Same as color code
Odor: Characteristic

Boiling point/range: decomposition starting from 300°C

Melting point/range: 140-170°C (284-338°F)

Autoignition Temperature: >300°C
Vapor Pressure: Negligible

Density: 0.905-0.930 g/cm³

Water Solubility: Insoluble Evaporation Rate: Negligible

VOC content (%): Negligible

Explosive Limits

upper: Not determined

lower: Not determined

Product Name: QR674K-00900 Page 5 of 8 Revision date: 28-May-2015



10. STABILITY AND REACTIVITY

Stability: Stable under ambient conditions. Hazardous polymerization does not occur.

Conditions to Avoid: Avoid temperatures above 300°C. Heating can result in the formation of gaseous

decomposition products, some of which may be hazardous. Do not exceed melt temperature recommendations in product literature. Purgings of hot material should be collected in small, flat, thin shapes and quenched with water to allow for rapid cooling. Do not allow product to remain in barrel at elevated temperatures for extended periods of time.

Hazardous Decomposition

Products:

Process vapors under recommended processing conditions may include trace levels of

hydrocarbons, carbon oxides.

11. TOXICOLOGICAL INFORMATION

LD50/oral/rat: >5000 mg/kg

LD50/dermal/rabbit: >2000 mg/kg

Subchronic Toxicity: No information available

Primary Irritation: Substance does not generally irritate and is only mildly irritating to the skin

Remarks: The toxicological data has been taken from products of similar composition

Special Studies: No Information

12. ECOLOGICAL INFORMATION

Ecotoxicity Effects: Ecological damages are not known or expected under normal

use. Small particles can have an effect on water and soil

organisms.

Other information: none.

13. DISPOSAL CONSIDERATIONS

Waste from residues / unused

products:

Where possible recycling is preferred to disposal or incineration. Dispose of in accordance

with local regulations.

Contaminated Packaging: Empty containers should be transported/delivered using a registered waste carrier for local

recycling or waste disposal.

EWC waste disposal no: 702 - waste from the manufacture, formulation, supply and use of plastics, synthetic rubber

and man-made fibres.

Product Name: QR674K-00900 Page 6 of 8 Revision date: 28-May-2015



14. TRANSPORT INFORMATION

Transport Classification:

Not regulated as hazardous for shipment, unless noted below, under current transportation

guidelines.

DOT

ADR/RID/ADN

IMDG

<u>ICAO</u>

IATA-DGR

15. REGULATORY INFORMATION

Further regulatory information can be requested via your local sales office.

International Inventories:

TSCA (USA): Listed
DSL (Canada): Listed
ENCS (Japan): Listed

IECSC (China): Not listed - Substance simplified process & product research development notification

approved under SABIC

KECL (Korea): Listed
PICCS (Philippines): Listed
AICS (Australia): Listed
NZIOC (New Zealand): Listed

REACH Information: For this product's REACH related information, please contact sds.info@sabic.com

Other Inventory Information:

A "Listed" entry above means all chemical components are on the respective inventory list and/or a qualifying exemption exists for one or more components. A "Not listed" entry above indicates one or more components is restricted from import or manufacture into that country/region. Articles are exempt from registration and are therefore not listed on the national chemical inventories.

HMIS Rating
Health: 0
Flammability: 1
Reactivity: 0

Product Name: QR674K-00900 Page 7 of 8 Revision date: 28-May-2015



16. OTHER INFORMATION

SABIC and brands marked with ™ are trademarks of SABIC or its subsidiaries or affiliates.

SDS Scope:

Europe: Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Regulation (EU) No. 453/2010. This document is also applicable in other countries and regions.

Prepared by:

Product Stewardship & Toxicology

DISCLAIMER: The information contained in the Safety Data Sheet is at the date of its issuance to the best of our knowledge correct according to the data available to us. The information is meant as a guideline for safe use, handling, disposal, storage and transport of products and does not imply any warranty (not implied nor explicitly) or specification. The Supplier shall to the extent permitted by law not be liable for any error or incorrectness in the information contained in this Safety Data Sheet. The information relates exclusively to the specified products, which may not be suitable for combination with other materials or use in processes other than those specifically described here.

End of Safety Data Sheet

Product Name: QR674K-00900 Page 8 of 8 Revision date: 28-May-2015