

SAFETY DATA SHEET

SABIC® PPcompound Elastomer modified Polypropylene (PP-EPDM) mineral filled

1. Identification of the substance/preparation and company/undertaking

Product name : SABIC® PPcompound Elastomer modified Polypropylene (PP-EPDM) mineral filled
Chemical product name : Polypropylene, EPDM and mineral modified
Supplier : SABIC Europe B.V.
P.O. Box 5151
6130 PD Sittard
The Netherlands
Emergency telephone number : **The Netherlands: +31 (0)46 476 55 55**
Recommended use : Industrial parts.

2. Composition/information on ingredients

Substance/preparation : Preparation

Within the present knowledge of the supplier, this product does not contain any hazardous ingredients in quantities requiring reporting in this section, in accordance with EU or national regulations.

3. Hazards identification

Human health hazards : Dust may cause mechanical irritation. Heated material can cause thermal burns.
Environmental hazards : Based on the available data of this product no hazardous properties are known.
Physical/chemical hazards : Combustible.

4. First-aid measures

Effects and symptoms

Inhalation : Over-exposure by inhalation may cause respiratory irritation. (coughing)
Ingestion : There is no known acute effect after over-exposure to this product.
Skin contact : Heated material can cause thermal burns resulting in pain, redness, blistering.
Eye contact : May cause eye irritation. (redness).

First-aid measures

Inhalation : If inhaled, remove to fresh air. Obtain medical attention if symptoms occur.
Ingestion : If swallowed, rinse mouth with water (only if the person is conscious). Obtain medical attention if symptoms occur.
Skin contact : Rinse with plenty of running water. Get medical attention.
Eye contact : Rinse with plenty of running water. Obtain medical attention if symptoms occur.
First aid facilities : No special recommendations.

5. Fire-fighting measures

Extinguishing media

Small fire

Suitable : Use dry chemical or CO₂.

Large fire

Suitable : Use water, foam or dry chemical powder.

Unusual fire/explosion hazards

: No specific hazard.

Hazardous thermal decomposition products

: In case of fire, may produce hazardous decomposition products such as carbon monoxide, carbon dioxide, (dense) black smoke, aldehydes, Organic acids.

Special fire-fighting procedures

: Fight fire from protected location or maximum possible distance. Keep the area surrounding the fire cool. Avoid contact with heated material.

Protection of fire-fighters

: Wear suitable protective clothing. Self-contained breathing apparatus.

Remarks

: The material burns slowly with high smoke density and flaming drips. Fine powder forms flammable and explosive mixtures in air. Use water spray to keep fire-exposed containers cool.

6. Accidental release measures

- Personal precautions** : Avoid creating dusty conditions and prevent wind dispersal. Use suitable protective equipment (section 8). Keep away from sources of ignition. Take precautionary measures against static discharges. Use explosion-proof electrical (ventilating, lighting and material handling) equipment.
- Environmental precautions** : No special measures required.
- Clean-up Methods**
- Small spill and leak** : Vacuum or sweep up material and place in a designated labelled waste container. Clean up affected area with a large amount of water.
- Large spill and leak** : Use explosion-proof electrical (ventilating, lighting and material handling) equipment.
- Note:** see section 8 for personal protective equipment and section 13 for waste disposal.

7. Handling and storage

- Handling** : Use with adequate ventilation. Local exhaust ventilation should be provided. Avoid creating dusty conditions and prevent wind dispersal. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Take measures against static discharge. Keep away from sources of ignition.
- Storage** : Store in a fireproof location. Keep away from incompatible materials and avoid specific conditions (See section 10). Containers should be grounded. Do not stack more than 2 pallets high in connection with risk of falling over. Keep in a dry place. Protect from (sun)light. Take precautionary measures against electrostatic discharges.
- Storage temperature** : Do not store above 80 °C.
- Remarks** : Precautions should be taken to prevent the formation of dusts in concentrations above flammable, explosive or occupational exposure limits. Avoid the creation of dust when handling and avoid all possible sources of ignition (spark or flame).

Note: See section 10 for stability and reactivity

8. Exposure controls/personal protection

- Engineering measures** : Use only with adequate ventilation. Local exhaust ventilation should be provided. Use explosion-proof electrical (ventilating, lighting and material handling) equipment.
- Hygiene measures** : When using do not eat, drink or smoke. Wash hands after handling compounds and before eating, smoking, using lavatory, and at the end of day.
- Personal protective equipment - Production scale**
- Respiratory system** : Wear dust protection mask P2.
- Skin and body** : Working clothes.
- Eyes** : Safety glasses with side shields.
- Hands** : When handling hot material, wear heat-resistant protective gloves that are able to withstand the temperature of molten product.
- Remarks** : A face shield must be worn in work involving spattering if a full mask is not required. In this case, other recommended use of eye protection is not required.

Advice on personal protection is applicable for high exposure levels. Select proper personal protection based on a risk assesment of the actual exposure situation.

9. Physical and chemical properties

- Physical state** : Solid. (Granular solid.)
- Colour** : Off-white.
- Odour** : Paraffin-like
- Melting point** : 145 to 170 °C
- Flash point** : >360 °C
- Lower explosion limit** : Not available.
- Upper explosion limit** : Not available.
- Auto-ignition temperature** : > 365 °C
- Density (g/cm³)** : 0.96 to 1.25 g/cm³
- Bulk density** : 650 to 970 kg/m³
- Solubility** : Insoluble in cold water
- Minimum ignition temperature** : 440 °C

10. Stability and reactivity

- Stability** : Stable under recommended storage and handling conditions (see section 7).
- Conditions to avoid** : Keep away from heat, sparks and flame. Take measures against static discharge. Exposure to (sun) light. Prevent formation of dust clouds.
- Materials to avoid** : oxidising agents.
- Hazardous decomposition products** : Highly dependent on temperature and environmental conditions, a variety of decomposition products may be formed, such as low molecular weight hydrocarbons and hydrocarbon oxidation products (acids, ketons, aldehydes).
- Remarks** : At processing temperatures some degree of thermal degradation may occur.

11. Toxicological information

Acute toxicity

Ingredient name	Test	Species	Route	Result
Polypropylene, EPDM and mineral modified	LD ₅₀	Rat	Oral	>5000 mg/kg

Chronic toxicity

- Remarks** : During heating and processing of the material small amounts of free monomer may evaporate resulting in airborne concentration that may cause irritating effects of the respiratory tract and nausea.

Note: See section 4 for effects and symptoms

12. Ecological information

- Ecotoxicity data** : Not available.

Ingredient name	Aquatic half-life	Photolysis	Biodegradability
Polypropylene, EPDM and mineral modified	-	-	Not readily

- Mobility** : For data on physical state and solubility see section 9.

13. Disposal considerations

- Methods of disposal (waste of residues; contaminated packaging)** : Waste must be disposed of in accordance with national and local environmental regulations.

14. Transport information

General information

- UN number** : Not regulated.

15. Regulatory information

EU regulations

- Risk phrases** : This product is not classified according to the EU regulations.

16. Other information

- Information** : Mr. H. Bril
Manager Product & Transport Safety
SABIC Europe B.V.
Telephone: +31 (0) 46 4762698
Email: henk.bril@SABIC-europe.com
- Internal code** : WW12969
- History**
- Date of printing** : 11 July 2005.

Date of issue : 11 July 2005**Version** : 5**Notice to reader**

All information supplied by or on behalf of the SABIC Europe companies in relation to its products, whether in the nature of data, recommendations or otherwise, is supported by research and believed reliable, but the relevant SABIC Europe company assumes no liability whatsoever in respect of application, processing or use made of the afore-mentioned information or products, or any consequence thereof. The user undertakes all liability in respect of the application, processing or use of the afore-mentioned information or product, whose quality and other properties he shall verify, or any consequence thereof. No liability whatsoever shall attach to any of the SABIC Europe companies for any infringement of the rights owned or controlled by a third party in intellectual, industrial or other property by reason of the application, processing or use of the afore-mentioned information or products by the user.

None of the materials referenced herein should be used and/or applied in any product, device or material used or for use as human body implant or otherwise within the human body.

Training advice : Before handling this substance/preparation, the personnel involved should be instructed by means of this safety data sheet.

Sources of key data : Literature data and/or investigation reports are available at the manufacturer.

Alterations compared to the previous version : Alterations compared to the previous version are marked with a little (blue) triangle.