

SAFETY DATA SHEET

Print date: 04-Jun-2015 Revision Number: 2 Revision date: 04-Jun-2015

1. IDENTIFICATION OF THE SUBSTANCE AND COMPANY

Trademark: SABIC® PS

Product Name: 125

Product Description: General purpose polystyrene [CASRN 9003-53-6]

Product Type: Commercial Product

Recommended use:May be used to produce molded or extruded articles or as a

component of other industrial products.

Company: SABIC

P.O. Box 5101 Riyadh 11422 Saudi Arabia

Manufacturer: SABIC

P.O. Box 5101

Riyadh 11422 Saudi Arabia

Emergency Telephone Number: KSA +966 (01) 225-8000

E-mail: sds.info@sabic.com

Website Address: www.sabic.com

2. HAZARDS IDENTIFICATION

The additives in this product (if any) are bound in a thermoplastic resin matrix. In accordance with GHS for the classification of the product, the hazard potential may be assessed with respect to the physico-chemical form and/or bioavailability of the individual components in the thermoplastic resin.

Where GHS classifications are shown below, these are based on the individual components in the thermoplastic resin matrix. Under the typical use conditions for the resin, these hazardous components are unlikely to contribute to workplace exposure. Please read the entire safety data sheet and/or consult an EHS professional for a complete understanding.

Classification

OSHA Regulatory Status

This product is not considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Route of exposure, mechanistic information and metabolism studies are pertinent to determining the relevance of an effect in humans (GHS section 1.3.2.4.9.4). Where appropriate, GHS classification can be specified as route-dependent. The presence of the White Mineral Oil does not lead to the thermoplastic pellets having a viscosity in the range of concern for aspiration hazard.

GHS-Labeling

Emergency Overview

Product Name: PS125-KSA Page 1 of 8 Revision date: 04-Jun-2015



Not classified

The product contains no substances which at their given concentration, are considered to be hazardous to health

 Appearance:
 Pellets
 Physical State:
 Solid
 Odor:
 None or slight

Hazards not otherwise classified (HNOC)

Not applicable

Other Information

Not applicable

Other hazards which do not result in classification:

SABIC Emergency Overview

- · Pellets with slight or no odor
- · Spilled material may create slipping hazard
- · Can burn in a fire creating dense, toxic smoke
- Molten plastic can cause severe thermal burns
- Fumes produced during melt processing may cause eye, skin, and respiratory tract irritation. Severe over-exposure may result in nausea, headache, chills, and fever. See below for additional effects.
- Secondary operations, such as grinding, sanding, or sawing can produce dust which may present an explosion or respiratory hazard.

Other Information: Cool skin rapidly with cold water after contact with molten material. Heating can release

hazardous gases. Hazardous fumes can also occur in post-processing operations.

Processing Issues: Processing vapors may cause irritation to the eyes, skin, and respiratory tract. In cases of

severe exposure, nausea and headache can also occur. Grease-like processing vapor condensates on ventilation ductwork, molds, and other surfaces can cause irritation and

injury to skin.

Aggravated Medical Conditions: MEDICAL RESTRICTIONS: There are no known health effects aggravated by exposure to

this product. However, certain sensitive individuals and individuals with respiratory impairments may be affected by exposure to components in the processing vapors.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Product Type Mixture

HAZARDOUS COMPONENTS:

Chemical Name	CAS Number	Weight %	GHS Classification (EC) No. 1272/2008 [CLP]:
White paraffin oil (petroleum)	8042-47-5	1-5	

The non-hazardous components and exact percentage (concentration) of the composition have been withheld as a trade secret.

This product consists primarily of high molecular weight polymers which are not expected to be hazardous. The ingredients in this product are present within the polymer matrix and are not expected to be hazardous.

Product Name: PS125-KSA Page 2 of 8 Revision date: 04-Jun-2015



4. FIRST AID MEASURES

If Inhalation: Move to fresh air in case of accidental inhalation of fumes from

overheating or combustion. If symptoms persist, call a physician.

On skin contact: Immediately cool the skin by rinsing with cold water after contact

with hot material. Wash off immediately with soap and plenty of

water. Consult a physician.

On contact with eyes: Immediately flush with plenty of water. After initial flushing,

remove any contact lenses and continue flushing for at least 15

minutes. If eye irritation persists, consult a specialist.

On ingestion: No hazards which require special first aid measures.

Precautions: Cool molten product on skin with plenty of water. Do not remove

solidified product. Do not peel polymer from the skin.

5. FIRE-FIGHTING MEASURES

Autoignition Temperature: 482 - 488°C (900 - 910°F)

Explosive Limits

upper: Not determined lower: Not determined

Suitable Extinguishing Media: Use dry chemical, CO2, water spray or "alcohol" foam. Water is

the best extinguishing medium. Carbon dioxide and dry chemical are not generally recommended because their lack of cooling capacity may permit re-ignition on larger resin fires (blobs, drools,

etc.).

Unsuitable Extinguishing Media for Safety Reasons: Do not use a solid water stream as it may scatter and spread fire.

Special Protective Equipment for Firefighters: In the event of fire, wear self-contained breathing apparatus (EU:

NEN-EN137).

Specific Hazards: Take precautionary measures against static discharges. During

processing, dust may form explosive mixture in air. Thermal decomposition can lead to release of irritating gases and vapors.

6. ACCIDENTAL RELEASE MEASURES

Clean up: Sweep up and shovel into suitable containers for disposal. Do not

create a powder cloud by using a brush or compressed air.

Personal Precautions: See section 8. If spilled, take caution, as material can cause

surfaces to become very slippery.

Environmental Precautions:Do not flush into surface water or sanitary sewer system. Material

should not be released into the environment.

Product Name: PS125-KSA Page 3 of 8 Revision date: 04-Jun-2015



7. HANDLING AND STORAGE

Handling:

Handle in accordance with good industrial hygiene and safety practices. Provide for appropriate exhaust ventilation and dust collection at machinery. Minimize dust generation and accumulation. Routine housekeeping should be instituted to ensure that dusts do not accumulate on surfaces. Dry powders can build static electricity charges when subjected to the friction of transfer and mixing operations. Provide adequate precautions, such as electrical grounding and bonding, or inert atmospheres.

Storage:

Store in a dry and cool area. Keep away from heat sources and sources of ignition. Keep away from direct sunlight.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure limits:

No components with information, unless noted below

Chemical Name	US OSHA PEL (8 Hr)	ACGIH	Canada - Alberta (8 Hr)	Mexico OEL Data	SABIC Recommend (8 Hr)*
White paraffin oil (petroleum) 8042-47-5	FRL_TWA: 5 mg/m³; TL_PEL: 5 mg/m³	No Information	No Information	LMPE-PPT: 5 mg/m³; LMPE-CT: 10 mg/m³	No Information

^{*}SABIC Recommended Exposure Limits have been established for certain chemicals.

Engineering Measures to Exposure:

In the case of hazardous fumes, wear self-contained breathing apparatus. Wear face-shield and protective suit for abnormal processing problems. Handle in accordance with good industrial hygiene and safety practice. Provide for appropriate exhaust ventilation at machinery.

Hand Protection:

Protective gloves should be worn, (EU: NEN-EN 374), When handling hot material, wear heat-resistant protective gloves that are able to withstand the temperature of molton resin

Eye Protection:

Safety glasses with side-shields. (EU: NEN-EN 165-166).

Respiratory Protection:

In the case of hazardous fumes, wear self contained breathing apparatus. In case of insufficient ventilation wear suitable

respiratory equipment. (EU: NEN-EN149).

Body Protection:

Long sleeved clothing (EU: NEN-EN 340-369-465)

Hygiene Measures:

When using, do not eat, drink or smoke.

Product Name: PS125-KSA Page 4 of 8 Revision date: 04-Jun-2015



9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State:SolidAppearance:PelletsColor:TransparentOdor:None or slight

Boiling point/range: Decomposition starting from 300°C (592°F)

Melting point/range: > 130 °C

 Autoignition Temperature:
 482 - 488°C (900 - 910°F)

 Flash Point:
 260 - 271°C (500 - 520°F)

Vapor Pressure:NegligibleDensity:1.05 g/cm³

Water Solubility: Insoluble Evaporation Rate: Negligible

VOC content (%): Negligible

Explosive Limits

upper:Not determinedlower:Not determined

10. STABILITY AND REACTIVITY

Stability: Stable under ambient conditions. Hazardous polymerization does

not occur.

Conditions to Avoid: Avoid temperatures above 300°C. Heating can result in the

formation of gaseous decomposition products, some of which

may be hazardous. Do not exceed melt temperature

recommendations in product literature. Purgings of hot material should be collected in small, flat, thin shapes and quenched with water to allow for rapid cooling. Do not allow product to remain in barrel at elevated temperatures for extended periods of time.

Materials to avoid: Oxidizing agents.

Hazardous Decomposition

Products:

Process vapors under recommended processing conditions may include trace levels of

hydrocarbons, carbon oxides, aldehydes, styrene.

Product Name: PS125-KSA Page 5 of 8 Revision date: 04-Jun-2015



11. TOXICOLOGICAL INFORMATION					
Acute Toxicity					
LD50/oral/rat:	>5000 mg/kg				
LD50/dermal/rabbit:	>2000 mg/kg				
Inhalation:	Pellet inhalation unlikely due to physical form.				
Eye Contact:	Resin particles, like other inert materials, are mechanically irritating to eyes.				
Skin Contact:	Not a hazard with pellets during normal industrial use.				
Ingestion:	Pellet ingestion unlikely due to physical form.				
Chronic Toxicity:	No information available.				
Subchronic Toxicity:	No information available				
Primary Irritation:	Substance does not generally irritate and is only mildly irritating to the skin.				
Remarks:	The toxicological data has been taken from products of similar composition.				
Special Studies:	No Information				
12. ECOLOGICAL INFORMATION					
Ecotoxicity Effects:	Ecological damages are not known or expected under normal use. Small particles can have an effect on water and soil organisms.				
Other information:	none.				
13. DISPOSAL CONSIDERATIONS					

Waste Disposal: Recycling is encouraged. Landfill or incinerate in accordance with federal, state and local requirements. Collected processing fume condensates and incinerator ash should be tested to determine waste classification.

Product Name: PS125-KSA Page 6 of 8 Revision date: 04-Jun-2015



14. TRANSPORT INFORMATION

Transport Classification:	Not regulated as hazardous for shipment, unless noted below, under current transportation guidelines.
DOT	
ADR/RID/ADN	
IMDG	
ICAO	
IATA-DGR	
MEXICO	
CANADA/TDG	

15. REGULATORY INFORMATION

Further regulatory information can be requested via your local sales office.

International Inventories:

TSCA (USA): Listed DSL (Canada): Listed ENCS (Japan): Listed IECSC (China): Listed KECL (Korea): Listed PICCS (Philippines): Listed Listed AICS (Australia): NZIoC (New Zealand): Listed

REACH Information: For this product's REACH related information, please contact sds.info@sabic.com

Other Inventory Information:

A "Listed" entry above means all chemical components are on the respective inventory list and/or a qualifying exemption exists for one or more components. A "Not listed" entry above indicates one or more components is restricted from import or manufacture into that country/region. Articles are exempt from registration and are therefore not listed on the national chemical inventories.

HMIS Rating
Health: 0
Flammability: 1
Reactivity: 0

Product Name: PS125-KSA Page 7 of 8 Revision date: 04-Jun-2015



16. OTHER INFORMATION

SABIC and brands marked with ™ are trademarks of SABIC or its subsidiaries or affiliates.

SDS Scope:

USA: Conforms to 29 CFR 1910.1200 (2012 OSHA Hazard Communication Standard) This document is also applicable in other countries and regions.

Prepared by:

Product Stewardship & Toxicology

DISCLAIMER: The information contained in the Safety Data Sheet is at the date of its issuance to the best of our knowledge correct according to the data available to us. The information is meant as a guideline for safe use, handling, disposal, storage and transport of products and does not imply any warranty (not implied nor explicitly) or specification. The Supplier shall to the extent permitted by law not be liable for any error or incorrectness in the information contained in this Safety Data Sheet. The information relates exclusively to the specified products, which may not be suitable for combination with other materials or use in processes other than those specifically described here.

End of Safety Data Sheet

Product Name: PS125-KSA Page 8 of 8 Revision date: 04-Jun-2015