+135-3858-6433 (GuangDong) +188-1699-6168 (ShangHai) +852-6957-5415 (HongKong)



LNP™ STAT-KON™ Compound CX01039 Europe-Africa-Middle East: COMMERCIAL

Also known as: LNP™ STAT-KON™ Compound PDX-C-01039

Product reorder name: CX01039

LNP STAT-KON CX01039 is a compound based on Polystyrene resin containing Proprietary Filler(s). Added features of this material include: Electrically Conductive.

YPICAL PROPERTIES ¹	TYPICAL VALUE	Unit	Standard
MECHANICAL			
Tensile Stress, break, 5 mm/min	41	MPa	ISO 527
Tensile Strain, break, 5 mm/min	1.3	%	ISO 527
Flexural Stress, break, 2 mm/min	71	MPa	ISO 178
Flexural Modulus, 2 mm/min	4900	MPa	ISO 178
IMPACT			
Izod Impact, unnotched 80*10*4 +23°C	10	kJ/m²	ISO 180/1U
Izod Impact, notched 80*10*4 +23°C	5	kJ/m²	ISO 180/1A
PHYSICAL			
Density	1.08	g/cm³	ISO 1183
ELECTRICAL			
Surface Resistivity	1.E+03 - 1.E+06	Ohm	ASTM D 257