

PLATAMID®

B 409 PELLETS

Platamid® B 409 Pellets

Copolyamide Hot Melt Adhesive / Extrusion Applications

Platamid® B 409 is a high molecular weight, high melting temperature range, partially crystalline copolyamide delivered in pellet form. The special interest of this product is the combination of high melting temperature and high melt viscosity. Platamid® B 409 can be applied out of a cresolic solution. The thermal activation of the hot melt layer can be accomplished by means of induction of hot air.

性能	干 / 已调节	单位	测试标准
流变性能			
熔体体积流动速度	7.2 / *	cm ³ /10min	ISO 1133
温度	200 / *	°C	-
	392 / *	°F	-
载荷	2.16 / *	kg	-
	4.76 / *	lb	-
热性能			
熔融温度, 10°C/min	178 / *	°C	ISO 11357-1/-3
其它性能			
密度	1100 / -	kg/m ³	ISO 1183
	1.1 / -	g/cm ³	

AVAILABLE GRADES

This grade is available:

- dried with lubricant (B 409 TL)
- undried with lubricant (B 409 FL)

PACKAGING

Platamid® B 409 TL is delivered in 25 kg sealed bags.

Platamid® B 409 FL is delivered in 25 kg sealed bags.

These grades are ready to be processed.

SHELF LIFE

Two years from the date of delivery. For any use above this limit, please refer to our technical services.

PLATAMID®

B 409 PELLETS

加工方法	
薄膜挤出成型	
供货形式	
粒料	
特殊性能	
Adhesive	
地区供应	
北美, 欧洲, 亚太, 中南美洲, 中东/非洲	