

PLATAMID®

H 1937 PELLETS

Platamid® H 1937 Pellets

Copolyamide Hot Melt Adhesive / Extrusion Applications

Platamid® H 1937 is a thermoplastic copolyamide adhesive available in pellet form for manufacture of hot melt film and webs by extrusion.

Platamid® H 1937 has good adhesion to all kinds of textile substrates based on native and synthetic fibers.

性能	干 / 已调节	单位	测试标准
流变性能			
熔体体积流动速度	18 / *	cm ³ /10min	ISO 1133
温度	160 / *	°C	-
	320 / *	°F	-
载荷	2.16 / *	kg	-
	4.76 / *	lb	-
热性能			
熔融温度, 10°C/min	102 / *	°C	ISO 11357-1/-3

AVAILABLE GRADES

This product is available:

- dried (H 1937 TA)

PACKAGING

- Platamid® H 1937 TA is delivered in 25 kg sealed bags.

This grade is ready to be processed.

SHELF LIFE

Two years from the date of delivery. For any use above this limit, please refer to our technical services.

加工方法	
薄膜挤出成型, Web Processing	
供货形式	
粒料	
特殊性能	
Adhesive	
地区供应	
北美, 欧洲, 亚太, 中南美洲, 中东/非洲	