

PLATAMID®

H 2513 PELLETS

Platamid® H 2513 Pellets
Copolyamide Hot Melt Adhesive

Platamid® H 2513 is a standard thermoplastic copolyamide hot melt adhesive available in pellet form. This low to medium melt viscosity, fast re-crystallizing grade is particularly suitable for manufacturing webs, nets, mono- and multi-filaments, and films by extrusion.

Platamid® H 2513 offers a very good adhesion to various polar substrates (thermoplastics, thermosets, metal, natural fibers, etc).

性能	干 / 已调节	单位	测试标准
流变性能			
熔体体积流动速度	26 / *	cm³/10min	ISO 1133
温度	160 / *	°C	-
	320 / *	°F	
载荷	2.16 / *	kg	-
	4.76 / *	lb	
热性能			
熔融温度, 10°C/min	128 / *	°C	ISO 11357-1/-3
其它性能			
密度	1070 / -	kg/m³	ISO 1183
	1.07 / -	g/cm³	

AVAILABLE GRADES

This grade is available dried with optical brightener (Platamid® H 2513 TA)

PACKAGING

Platamid® H 2513 is delivered in 25 kg sealed bags and 500 kg sealed big bags (GRVS).

SHELF LIFE

Two years from the date of delivery. For any use above this limit, please refer to our technical services.

供货形式	
粒料	
特殊性能	
Adhesive	
地区供应	
北美, 欧洲, 亚太, 中南美洲, 中东/非洲	