

PLATAMID®

H 2516 PELLETS

Platamid® H 2516 Pellets

Copolyamide Hot Melt Adhesive

Platamid® H 2516 is a thermoplastic copolyamide hot melt adhesive available in pellet form. This fast re-crystallizing grade has been developed to manufacture hot-melt webs, nets and mono- and multi-filaments.

Platamid® H 2516 offers a very good adhesion to all kinds of textile substrates based on native and synthetic fibers.

Additionally Platamid® H 2516 provides elastomeric properties and high water vapor transmission rate.

性能	干 / 已调节	单位	测试标准
流变性能			
熔体体积流动速度	85 / *	cm³/10min	ISO 1133
温度	160 / *	°C	-
	320 / *	°F	-
载荷	2.16 / *	kg	-
	4.76 / *	lb	-
热性能			
熔融温度, 10°C/min	108 / *	°C	ISO 11357-1/-3

AVAILABLE GRADES

This grade is available:

- Undried with optical brightener (H 2516 FA)

PACKAGING

Platamid® H 2516 FA is delivered in 500 kg sealed bags (GRVS) and 500 kg sealed rigid container (GRVC). These grades are ready to be processed.

SHELF LIFE

Two years from the date of delivery. For any use above this limit, please refer to our technical services.

加工方法	
Melt Spinning	
供货形式	
粒料	
特殊性能	
Adhesive	
地区供应	
北美, 欧洲, 亚太, 中南美洲, 中东/非洲	