

PLATAMID® H 2707 PELLETS

Platamid® H 2707 Pellets
Copolyamide Hot Melt Adhesive / Extrusion Applications

Platamid® H 2707 is a standard thermoplastic copolyamide hot melt adhesive available in pellet form. This medium to high melt viscosity grade is particularly suitable for manufacturing webs, mono- and multi-filaments, and films by extrusion. Platamid® H 2707 offers a good adhesion at low fusing conditions to various polar substrates (thermoplastics, thermosets, metal, natural fibers, etc.).

性能	干 / 已调节	单位	测试标准
流变性能			
熔体体积流动速度	2 / *	cm³/10min	ISO 1133
温度	160 / *	°C	-
	320 / *	°F	-
载荷	2.16 / *	kg	-
	4.76 / *	lb	-
热性能			
熔融温度, 10°C/min	102 / *	°C	ISO 11357-1/-3
其它性能			
密度	1060 / -	kg/m³	ISO 1183
	1.06 / -	g/cm³	

AVAILABLE GRADES

This grade is available:

- dried (H 2707 T)

PACKAGING

- Platamid® H 2707 T is delivered in 25 kg sealed bags.

SHELF LIFE

Two years from the date of delivery. For any use above this limit, please refer to our technical services.

RENEWABLE CARBON CONTENT

20% (calculated)

加工方法	
Melt Spinning	
供货形式	
粒料	
特殊性能	
Adhesive, 生物基	
地区供应	
北美, 欧洲, 亚太, 中南美洲, 中东/非洲	