

PLATAMID®

H 38 PELLETS

Platamid® H 38 Pellets

Copolyamide Hot Melt Adhesive

Platamid® H 38 is a standard thermoplastic copolyamide hot melt adhesive available in pellet form. This low to medium melt viscosity grade is particularly suitable for manufacturing webs, nets, mono- and multi-filaments and films by extrusion.

Platamid® H 38 offers very good adhesion to various polar substrates (thermoplastics, thermosets, metal, natural fibers, etc).

性能	干 / 已调节	单位	测试标准
流变性能			
熔体体积流动速度	23 / *	cm³/10min	ISO 1133
温度	160 / *	°C	-
	320 / *	°F	-
载荷	2.16 / *	kg	-
	4.76 / *	lb	-
热性能			
熔融温度, 10°C/min	109 / *	°C	ISO 11357-1/-3
其它性能			
密度	1.07 / 1.07	kg/m³	ISO 1183
	0.00107 / 0.00107	g/cm³	

AVAILABLE GRADES

This grade is available:

- dried with optical brightener (H 38 TA)
- undried with optical brightener (H 38 FA)

PACKAGING

Platamid® H 38 TA is delivered in 25 kg sealed bags.

Platamid® H 38 FA is delivered in 500 kg sealed big bags (GRVS).

These grades are ready to be processed

SHELF LIFE

Two years from the date of delivery. For any use above this limit, please refer to our technical services.

PLATAMID®

H 38 PELLETS

加工方法	
Web Processing	
供货形式	
粒料	
地区供应	
北美, 欧洲, 亚太, 中南美洲, 中东/非洲	