

PLATAMID® HX 2544 POWDER

Platamid® HX 2544 Powder
Copolyamide Hot Melt Adhesive / Textile Applications

Platamid® HX 2544 Powder is a low melt viscosity copolyamide adhesive powder for the production of fusible interlinings. Platamid® HX 2544 Powder is particularly useful where low and short bonding conditions are required for leather and fur. Platamid® HX 2544 Powder has good dry cleaning resistance and washing resistance up to 60°C. Platamid® HX 2544 Powder has a renewable carbon content of 60% (internal method).

性能	干 / 已调节	单位	测试标准
流变性能			
熔体体积流动速度	104 / *	cm³/10min	ISO 1133
温度	160 / *	°C	-
	320 / *	°F	-
载荷	2.16 / *	kg	-
	4.76 / *	lb	-
热性能			
熔融温度, 10°C/min	95 / *	°C	ISO 11357-1/-3

AVAILABLE GRADES

This grade is available in different grain sizes:

- Platamid® HX 2544 PA80 (0-80 µm paste dot)
- Platamid® HX 2544 PTA 170 (80-170 µm double dot)
- Platamid® HX 2544 PRA 170 (80-170 µm double dot)

PACKAGING

- Platamid® HX 2544 Powder is delivered in 25 kg sealed bags.

SHELF LIFE

Two years from the date of delivery. For any use above this limit, please refer to our technical services.

RENEWABLE CARBON CONTENT

60% (internal method)

加工方法	
Scattering, Paste, Double Dot	
供货形式	
粉料	
特殊性能	
Adhesive, 生物基	
地区供应	
北美, 欧洲, 亚太, 中南美洲, 中东/非洲	