

PLATAMID® HX 2632 PELLETS

Platamid® HX 2632 Pellets
Copolyamide Hot Melt Adhesive

Platamid® HX 2632 Pellets is a thermoplastic copolyamide hot melt adhesive available in pellet form. This very low melt viscosity grade is particularly suitable for manufacturing webs, nets, mono- and multi-filaments by extrusion and then converted into very high viscous product providing additional properties as the bonding temperature resistance. A controlled activation of crosslinking reactions can be achieved during a processing step by various means such as peroxides, UV and e-beams.

Platamid® HX 2632 Pellets offers a very good adhesion at low fusing conditions to various kind of polar substrates (thermoplastics, thermosets, metal, natural fibers, etc.).

性能	干 / 已调节	单位	测试标准
流变性能			
熔体体积流动速度	70 / *	cm ³ /10min	ISO 1133
温度	160 / *	°C	-
	320 / *	°F	-
载荷	2.16 / *	kg	-
	4.76 / *	lb	-
热性能			
熔融温度, 10°C/min	117 / *	°C	ISO 11357-1/-3

AVAILABLE GRADES

This grade is available:

- undried with optical brightener (HX 2632 FA)

PACKAGING

- Platamid® HX 2632 FA is delivered in 500 kg sealed bags (GRVS) or in 25 kg sealed bags.

These grades are ready to be processed.

SHELF LIFE

Two years from the date of delivery. For any use above this limit, please refer to our technical services.

加工方法	
薄膜挤出成型, Melt Spinning, Web Processing	
供货形式	
粒料	
特殊性能	
Adhesive	
地区供应	
北美, 欧洲, 亚太, 中南美洲, 中东/非洲	