

PLATAMID®

HX 2651 PELLETS

Platamid® HX 2651 Pellets
Copolyamide Hot Melt Adhesive / Extrusion Applications

Platamid® HX 2651 Pellets is a standard thermoplastic copolyamide hot melt adhesive available in pellet form. This low melt viscosity grade is particularly suitable for manufacturing webs and nets by extrusion. Platamid® HX 2651 Pellets offers good adhesion to various polar substrates (thermoplastics, thermosets, metal, natural fibers, etc.) thanks to its amine functionality groups.

| 性能 | 干 / 已调节 | 单位 | 测试标准 |
|----------------|------------|-----------|----------------|
| 流变性能 | | | |
| 熔体体积流动速度 | 36 / * | cm³/10min | ISO 1133 |
| 温度 | 130 / * | °C | - |
| | 266 / * | °F | - |
| 载荷 | 2.16 / * | kg | - |
| | 4.76 / * | lb | - |
| 热性能 | | | |
| 熔融温度, 10°C/min | 105 / * | °C | ISO 11357-1/-3 |

AVAILABLE GRADES

This grade is available:

- Platamid® HX 2651 FA Pellets(undried)

PACKAGING

- Platamid® HX 2651 is delivered in 25 kg sealed bags.

SHELF LIFE

Two years from the date of delivery. For any use above this limit, please refer to our technical services.

| | |
|---------------------------------------|--|
| 加工方法 | |
| 薄膜挤出成型, Melt Spinning, Web Processing | |
| 供货形式 | |
| 粒料 | |
| 特殊性能 | |
| Adhesive | |
| 地区供应 | |
| 北美, 欧洲, 亚太, 中南美洲, 中东/非洲 | |