

PLATAMID®

HX 2651 POWDER

Platamid® HX 2651 Powder

Copolyamide Hot Melt Adhesive / Textile Applications

Platamid® HX 2651 Powder is a very high melt viscosity standard copolyamide adhesive powder for the production of fusible interlinings.

Platamid® HX 2651 Powder offers excellent laundry resistance up to 40°C. This super fluid product permits better penetration to treated fabric.

性能	干 / 已调节	单位	测试标准
流变性能			
熔体体积流动速度	195 / *	cm³/10min	ISO 1133
温度	160 / *	°C	-
	320 / *	°F	-
载荷	2.16 / *	kg	-
	4.76 / *	lb	-
热性能			
熔融温度, 10°C/min	115 / *	°C	ISO 11357-1/-3

AVAILABLE GRADES

This powder grade is available in different grain sizes:

- Platamid® HX 2651 PA80 (0-80 µm paste dot)
- Platamid® HX 2651 PTA 170 (80-170 µm double dot)
- Platamid® HX 2651 PRA 170 (80-170 µm double dot)
- Platamid® HX 2651 PTA 60 (80-120 µm powder dot)

PACKAGING

- Platamid® HX 2651 powder is delivered in 20 kg sealed bags.

SHELF LIFE

Two years from the date of delivery. For any use above this limit, please refer to our technical services.

加工方法	
Scattering, Paste, Double Dot	
供货形式	
粉料	
特殊性能	
Adhesive	
地区供应	
北美, 欧洲, 亚太, 中南美洲, 中东/非洲	