

PLATAMID® M 1422 PELLETS

Platamid® M 1422 Pellets
Copolyamide Hot Melt Adhesive / Extrusion Applications

Platamid® M 1422 Pellets is a standard thermoplastic copolyamide hot melt adhesive available in pellet form and is used in solvent based processes.
Platamid® M 1422 Pellets is a semi-crystalized copolyamide product which has been developed for use in the wire coating industry.

性能	干 / 已调节	单位	测试标准
流变性能			
熔体体积流动速度	30 / *	cm³/10min	ISO 1133
温度	230 / *	°C	-
	446 / *	°F	-
载荷	2.16 / *	kg	-
	4.76 / *	lb	-
热性能			
熔融温度, 10°C/min	120 / *	°C	ISO 11357-1/-3

AVAILABLE GRADES

This product is available:

- undried (M 1422 F)
- undried (M 1422/1 F)

PACKAGING

- Platamid® M 1422 F and M 1422/1 F are delivered in 25 kg sealed bags.

These grades are ready to be processed.

SHELF LIFE

Two years from the date of delivery. For any use above this limit, please refer to our technical services.

加工方法	
薄膜挤出成型	
供货形式	
粒料	
特殊性能	
Adhesive	
地区供应	
北美, 欧洲, 亚太, 中南美洲, 中东/非洲	