

Technical Data Sheet

Alathon L5845



High Density Polyethylene

Product Description

Alathon L5845 is a medium molecular weight high density homopolymer for use in blown film applications. Typical applications include paper replacement, coextrusions, slit tape, and laminations.

Application	Bags & Pouches; Barrier Film; Food Packaging Film; Lamination Film; Nets
Market	Flexible Packaging
Processing Method	Blown Film; Cast Film; Tapes & Raffia
Attribute	General Purpose; Good Abrasion Resistance; Good Organoleptic Properties; High Density; High Stiffness; Low Gel

Typical Properties	Nominal Value	English Units	Nominal Value	SI Units	Test Method
Physical					
Melt Flow Rate, (190 °C/2.16 kg)	0.45	g/10 min	0.45	g/10 min	ASTM D1238
Density, (23 °C)	0.958	g/cm ³	0.958	g/cm ³	ASTM D1505
Film					
Tensile Strength at Break					
MD	7900	psi	54.5	MPa	ASTM D882
TD	4600	psi	31.7	MPa	ASTM D882
Tensile Strength at Yield					
MD	3800	psi	26.2	MPa	ASTM D882
TD	3900	psi	26.9	MPa	ASTM D882
Tensile Elongation at Break					
MD	750	%	750	%	ASTM D882
TD	850	%	850	%	ASTM D882
Secant Modulus					
MD	134000	psi	925	MPa	ASTM D882
TD	184000	psi	1270	MPa	ASTM D882
Elmendorf Tear Strength					
MD	25	g	25	g	ASTM D1922
TD	1200	g	1200	g	ASTM D1922