

Technical Data Sheet

**Hostacom BB 1161 F/M D72703**



Polypropylene Compounds

**Product Description**

Hostacom BB 1161 F M D72703 is a 12% talc filled PP copolymer, with high melt flow rate, and UV resistance, excellent processability and high stiffness. The product reflects the latest advancements in resin synthesis and compounding technology. The product is also available as a customized color matched, pellet form. This grade is delivered in D72703 color version.

*This grade is not intended for medical, pharmaceutical, food and drinking water applications.*

<b>Status</b>	Commercial: Active
<b>Availability</b>	Europe
<b>Application</b>	Interior Trims
<b>Market</b>	Automotive
<b>Processing Method</b>	Injection Molding
<b>Attribute</b>	Good Color Stability; Good Processability; High Flow; Medium Impact Resistance; UV Resistant

Typical Properties	Nominal Value	Units	Test Method
<b>Physical</b>			
Melt Flow Rate, (230 °C/2.16 kg)	28	g/10 min	ISO 1133-1
Density, (23 °C)	1	g/cm <sup>3</sup>	ISO 1183-1/A
<b>Mechanical</b>			
Flexural Modulus, (23 °C, Tech. A)	2000	MPa	ISO 178/A1
<b>Impact</b>			
Charpy Impact Strength - Notched, (23 °C)	4	kJ/m <sup>2</sup>	ISO 179-1/1eA