

## Technical Data Sheet

### *Moplen* HP520M



Polypropylene, Homopolymer

#### Product Description

*Moplen* HP520M is a polypropylene homopolymer resin, with good optical properties, low gels and good stiffness for films, and excellent compatibility with multi-layer film constructions. Typical customer applications are core layer for co-extrusion cast films, and ribbon tape extrusion.

<b>Application</b>	Food Packaging Film; Lamination Film
<b>Market</b>	Consumer Products; Flexible Packaging
<b>Processing Method</b>	Cast Film
<b>Attribute</b>	Good Optical Properties; Good Stiffness; Low Gel

Typical Properties	Nominal Value	Units	Test Method
<b>Physical</b>			
Melt Flow Rate, (230 °C/2.16 kg)	8	g/10 min	ASTM D1238
Density	0.90	g/cm <sup>3</sup>	ASTM D792
<b>Mechanical</b>			
Flexural Modulus	1550	MPa	ASTM D790
Tensile Strength at Yield	35	MPa	ASTM D638
Tensile Elongation at Yield	10	%	ASTM D638
<b>Impact</b>			
Notched Izod Impact Strength, (23 °C)	28	J/m	ASTM D256
<b>Thermal</b>			
Deflection Temperature Under Load	105	°C	ASTM D648