

Technical Data Sheet

Moplen HP648T P9T



Polypropylene, Homopolymer

Product Description

Moplen HP648T P9T is a homopolymer used in injection molding. This grade is characterized by a high flow, medium stiffness combined with a Nucleation and an antistatic addition.

Moplen HP648T P9T is typically used by customers in houseware, TWIM food and Non-food containers.

This grade is not intended for medical and pharmaceutical applications.

Application	Housewares; TWIM Food Containers; TWIM Non-food Containers
Market	Rigid Packaging
Processing Method	Injection Molding
Attribute	Contains Antistat; Good Stiffness; High Flow; Nucleated

Typical Properties	Nominal Value	Units	Test Method
Physical			
Melt Flow Rate, (230 °C/2.16 kg)	53	g/10 min	ISO 1133-1
Density, (23 °C)	0.90	g/cm ³	ISO 1183-1
Mechanical			
Tensile Modulus	1600	MPa	ISO 527-1, -2
Tensile Stress at Yield	35	MPa	ISO 527-1, -2
Tensile Strain at Break	>50	%	ISO 527-1, -2
Tensile Strain at Yield	8	%	ISO 527-1, -2
Impact			
Charpy Impact Strength - Notched, (23 °C, Type 1, Edgewise, Notch A)	2	kJ/m ²	ISO 179
Thermal			
Vicat Softening Temperature, (A50)	154	°C	ISO 306
Heat Deflection Temperature B, (0.45 MPa, Unannealed)	95	°C	ISO 75B-1, -2