

## Technical Data Sheet

### Hostalen PP H2483



Polypropylene, Impact Copolymer

#### Product Description

Hostalen PP H2483 is a natural polypropylene copolymer with a good mechanical properties balance. The product is typically used by customers in the application of solid and structured wall pipes for underground drainage and sewage systems. The product can enable customers to reach high pipe ring stiffness and good impact strength for installations at room temperature and in particular at sub-zero temperatures. For further details about the suitable applications for this material please contact LyondellBasell.

This grade is not intended for medical and pharmaceutical applications.

<b>Application</b>	Soil & Waste Pipe
<b>Market</b>	Pipe
<b>Processing Method</b>	Pipe; Sheet
<b>Attribute</b>	Antioxidant; Block Copolymer

Typical Properties	Nominal Value	Units	Test Method
<b>Physical</b>			
Melt Flow Rate			
(230 °C/2.16 kg)	0.3	g/10 min	ISO 1133-1
(230 °C/5.0 kg)	1.3	g/10 min	ISO 1133-1
(190 °C/5.0 kg)	0.5	g/10 min	ISO 1133-1
Density	0.90	g/cm <sup>3</sup>	ISO 1183-1
<b>Mechanical</b>			
Tensile Modulus, (23 °C)	1800	MPa	ISO 527-1, -2
Tensile Stress at Yield	32	MPa	ISO 527-1, -2
Tensile Strain at Yield	8	%	ISO 527-1, -2
<b>Impact</b>			
Charpy Impact Strength - Notched			
(23 °C)	60	kJ/m <sup>2</sup>	ISO 179
(0 °C)	15	kJ/m <sup>2</sup>	ISO 179
(-20 °C)	6	kJ/m <sup>2</sup>	ISO 179
(-30 °C)	4.3	kJ/m <sup>2</sup>	ISO 179
<b>Thermal</b>			
Oxidation Induction Time, (200 °C)	30	min	ISO 11357-6