

Technical Data Sheet

Moplen EP640T



Polypropylene, Impact Copolymer

Product Description

Moplen EP640T is a polypropylene impact copolymer with optimized balance of stiffness and toughness, low warpage, and high impact strength at low temperature. Typical customer applications are injection molding of electrical appliance parts, thin-wall packaging, and base resin of compounds for automobiles.

Application	Cooling Appliances; Dishwashing Appliances; Housewares; Opaque Containers; Washing Appliances
Market	Automotive; Consumer Products; Electrical / Electronics; Rigid Packaging
Processing Method	Injection Molding
Attribute	High Flow; High Stiffness; Impact Copolymer

Typical Properties	Nominal Value	Units	Test Method
Physical			
Melt Flow Rate, (230 °C/2.16 kg)	51	g/10 min	ASTM D1238
Density	0.90	g/cm ³	ASTM D792
Mechanical			
Flexural Modulus	1700	MPa	ASTM D790
Tensile Strength at Yield	28	MPa	ASTM D638
Tensile Elongation at Yield	5	%	ASTM D638
Impact			
Notched Izod Impact Strength			
(23 °C)	70	J/m	ASTM D256
(-20 °C)	30	J/m	ASTM D256
Hardness			
Rockwell Hardness, (R-Scale)	98		ASTM D785
Thermal			
Vicat Softening Point	150	°C	ASTM D1525
Deflection Temperature Under Load, (0.46 N/mm ²)	125	°C	ASTM D648