

Technical Data Sheet

Moplen EP642S



Polypropylene, Impact Copolymer

Product Description

Moplen EP642S is a polypropylene impact copolymer with an optimized balance of stiffness and toughness, high flowability and low warpage. Typical customer applications are injection molding of Thin Wall (TWIM) Containers, housewares, and as base resin for automotive compounding.

Application	Housewares; Opaque Containers
Market	Automotive; Consumer Products
Processing Method	Injection Molding
Attribute	Good Processability; High Flow; High Heat Resistance; High Stiffness; Impact Copolymer

Typical Properties	Nominal Value	Units	Test Method
Physical			
Melt Flow Rate, (230 °C/2.16 kg)	37	g/10 min	ASTM D1238
Density	0.90	g/cm ³	ASTM D792
Mechanical			
Flexural Modulus	1600	MPa	ASTM D790
Tensile Strength at Yield	28	MPa	ASTM D638
Tensile Elongation at Yield	4	%	ASTM D638
Impact			
Notched Izod Impact Strength			
(23 °C)	80	J/m	ASTM D256
(-20 °C)	40	J/m	ASTM D256
Hardness			
Rockwell Hardness, (R-Scale)	98		ASTM D785
Thermal			
Vicat Softening Point	150	°C	ASTM D1525
Deflection Temperature Under Load, (0.46 N/mm ²)	125	°C	ASTM D648