



Hifax CA 1210 G 1740

Compounded Polyolefin

Product Description

Hifax CA 1210 G 1740 is a 10% talc filled PP copolymer, with high flowability and good UV resistance. The product is available in different color matched, pellet form. This grade is delivered in 1740 color version.

This grade is not intended for medical, pharmaceutical, food and drinking water applications.

Product Characteristics

Status	Commercial	
Availability	Europe	(1)
Processing Method	Injection molding	
Features	Flowability, UV resistance.	
Typical Customer Applications	Used for outdoor/exterior applications.	

Typical Properties	Method	Value	Unit
Physical			
Melt Flow Rate (230 °C, 2.16 kg)	ISO 1133	37	g/10 min
Density (23 °C)	ISO 1183-1/A	0.98	g/cm ³
Mechanical			
Flexural Modulus (23 °C) Tech. A	ISO 178/A1	1060	MPa
Thermal			
Vicat Softening Temperature A (10 N)	ISO 306	116	°C

Product Storage and Handling

- Product should be stored in dry conditions at temperatures below 50°C and protected from UV-light.
- Improper storage may bring damage to the packaging and can negatively affects on the quality of this product
- Keep material completely dry for good processing.

Notes

Typical properties; not to be construed as specifications.

(1) : Here is indicated the region where the material is produced. For importation or demand of a local equivalent grade, please contact our Sales Representatives.