



## Hostacom X M3 V05 102942

### Compounded Polyolefin

#### Product Description

Hostacom X M3 V05 102942 is a 26% mineral filled PP copolymer, with high melt flow rate, high stiffness and good mould release. Product is available as a customized color matched, pellet form. This grade is delivered in 102942 color version.

*This grade is not intended for medical, pharmaceutical, food and drinking water applications.*

#### Product Characteristics

<b>Status</b>	Commercial	
<b>Availability</b>	Europe	(1)
<b>Processing Method</b>	Injection molding	
<b>Features</b>	High melt flow rate, stiffness, mould release.	
<b>Typical Customer Applications</b>	Used for automotive under-the-hood and battery cases.	

Typical Properties	Method	Value	Unit
<b>Physical</b>			
Melt Flow Rate (230 °C, 2.16 kg)	ISO 1133	14	g/10 min
Density (23 °C)	ISO 1183-1/A	1.09	g/cm <sup>3</sup>
<b>Mechanical</b>			
Tensile Stress at Yield (23 °C)	ISO 527-1, -2	42	MPa
Flexural Modulus (23 °C) Tech. A	ISO 178/A1	3100	MPa

#### Product Storage and Handling

- Product should be stored in dry conditions at temperatures below 50°C and protected from UV-light.
- Improper storage may bring damage to the packaging and can negatively affects on the quality of this product
- Keep material completely dry for good processing.

#### Notes

Typical properties; not to be construed as specifications.

(1) : Here is indicated the region where the material is produced. For importation or demand of a local equivalent grade, please contact our Sales Representatives.