



**Product Data Sheet &  
General Processing Conditions**

**RTP 799 A X 123737 C NS  
Low Density Polyethylene (LDPE)**

**PROPERTIES & AVERAGE VALUES OF INJECTION MOLDED SPECIMENS**

<b>PERMANENCE</b>	<b>English</b>	<b>SI Metric</b>	<b>ASTM TEST</b>
Specific Gravity	0.89	0.89	D 792
Melt Flow Rate @ 190 °C, / 2.16 kg	30.00 g/10 min	30.00 g/10 min	D 1238

**PROPERTY NOTES**

Data herein is typical and not to be construed as specifications.  
Unless otherwise specified, all data listed is for natural or black colored materials. Pigments can affect properties.

**GENERAL PROCESSING FOR INJECTION MOLDING**

	<b>English</b>	<b>SI Metric</b>
Injection Pressure	10000 - 15000 psi	69 - 103 MPa
Melt Temperature	380 - 450 °F	193 - 232 °C
Mold Temperature	70 - 150 °F	21 - 66 °C
Drying	2 hrs @ 175 °F	2 hrs @ 79 °C

Page: 2

Data Sheet for: RTP 799 A X 123737 C NS  
NATURAL

---

SECTION III - HAZARDS IDENTIFICATION (cont.)

---

EFFECTS OF OVEREXPOSURE: (cont.)

respiratory tract.

CHRONIC EFFECTS: None known for this compound.

---

SECTION IV - FIRST AID MEASURES

---

FIRST AID:

EYES: Flush with water. Consult physician if symptoms persist.

SKIN: Wash with soap and water. For thermal burns, immediately flush with cold water. Do not attempt to remove polymer from skin. Obtain medical attention.

INHALATION: Leave exposed area and seek fresh air. If irritation persists seek medical attention.

---

SECTION V - FIREFIGHTING MEASURES

---

FLAMMABILITY CLASS: 1      FLASH POINT: None      LEL: None      UEL: None

EXTINGUISHING MEDIA:

Water spray and foam. Water spray is preferred.

Dry chemical and CO2 are not generally recommended due to their lack of cooling capacity which may allow re-ignition.

SPECIAL FIREFIGHTING PROCEDURES:

Persons exposed to products of combustion should wear NIOSH approved self contained breathing apparatus and full protective equipment.

UNUSUAL FIRE & EXPLOSION HAZARDS:

This compound has no unusual fire or explosion hazards.

---

SECTION VI - ACCIDENTAL RELEASE MEASURES

---

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

Spilled pellets may cause a slipping hazard. Sweep area as needed.

---

SECTION VII - HANDLING AND STORAGE

---

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING:

Store in a dry, sprinkler equipped warehouse.

Product as shipped is not a combustible dust. Mechanical  
(cont.)

Page: 3

Data Sheet for: RTP 799 A X 123737 C NS  
NATURAL

SECTION VII - HANDLING AND STORAGE (cont.)

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: (cont.)  
handling can cause the formation of dusts. To reduce the risk for dust explosion do not permit dust to accumulate.

OTHER PRECAUTIONS:  
Proper purging and shut down procedures should be followed to avoid overheating of this compound.

SECTION VIII - EXPOSURE CONTROLS/PERSONAL PROTECTION

RESPIRATORY PROTECTION:  
A NIOSH approved respirator is recommended for protection against processing fumes, or from dust generated from grinding, sanding, or sawing operations.

VENTILATION:  
Local exhaust is preferred.

PROTECTIVE GLOVES:  
Canvas or cotton gloves are recommended.

EYE PROTECTION:  
Safety glasses with side shields are recommended.

OTHER PROTECTIVE EQUIPMENT:  
None.

SECTION IX - PHYSICAL AND CHEMICAL PROPERTIES

BOILING RANGE: None	VAPOR DENSITY: Non Volatile
EVAP. RATE: Unavailable	SPECIFIC GRAVITY: 0.91

VOLATILES: volume %: N/AP weight %: N/AP

APPEARANCE: Cylindrical Pellets No Odor

SECTION X - STABILITY AND REACTIVITY

STABILITY:	<input type="checkbox"/> Unstable	<input checked="" type="checkbox"/> Stable
HAZARDOUS POLYMERIZATION:	<input type="checkbox"/> May Occur	<input checked="" type="checkbox"/> Will Not Occur

INCOMPATIBILITY:  
Strong oxidizing agents. May also burn or react violently with fluorine/oxygen mixtures that contain 50-100% fluorine.

CONDITIONS TO AVOID:  
Avoid temperatures above 325 C (617 F).

Page: 4

Data Sheet for: RTP 799 A X 123737 C NS  
NATURAL

---

SECTION X - STABILITY AND REACTIVITY (cont.)

---

HAZARDOUS DECOMPOSITION PRODUCTS:

Carbon monoxide, carbon dioxide, nitrogen oxides, acrolein, formaldehyde, olefinic and paraffinic compounds, organic acids, ketones, aldehydes, and hydrocarbons.

---

SECTION XI - TOXICOLOGICAL INFORMATION

---

TOXICITY DATA:

No specific toxicological information is available.

---

SECTION XII - ECOLOGICAL INFORMATION

---

ECOTOXICITY:

No specific ecological information is available. This material is considered to be non-biodegradable.

---

SECTION XIII - DISPOSAL CONSIDERATIONS

---

WASTE DISPOSAL METHOD:

The pellets, regrind, and purge of this material are non-hazardous and may be discarded in accordance with state, federal, and local regulations.

---

SECTION XIV - TRANSPORT INFORMATION

---

D.O.T. SHIPPING INFORMATION:

Not regulated under US Department of Transportation.

---

SECTION XV - REGULATORY INFORMATION

---

SARA TITLE III SECTION 313:

This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right To Know Act of 1986 and of 40 CFR 372:

NONE

Page: 5

Data Sheet for: RTP 799 A X 123737 C NS  
NATURAL

---

SECTION XVI - OTHER INFORMATION

---

MSDS DISCLAIMER

Miller Waste Mills Inc. believes that the information contained herein is accurate as of the date hereof. HOWEVER, NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESSED OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR OF ANY OTHER NATURE ARE MADE HEREIN AS TO THE INFORMATION PROVIDED OR THE PRODUCT TO WHICH THE INFORMATION REFERS. The health and safety precautions contained herein may not be adequate for all individuals and/or situations. It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. Nothing contained herein shall be construed as a license for the use of any product in a manner that would infringe existing patents.