



组件 - 塑料  
UL 档案号: E84658

RTP CO  
580 E FRONT ST  
PO BOX 5439  
WINONA, MN 55987 United States



RTP 301 FR UV (f1)

Polycarbonate (PC), pellets, glass fiber reinforced

(f1) - Suitable for outdoor use with respect to exposure to Ultraviolet Light, Water Exposure and Immersion in accordance with UL 746C.

可燃性	值	测试方法
UL 阻燃等级		UL 94
1.5 mm, ALL	V-0	IEC 60695-11-10, -20
3.0 mm, ALL	V-0, 5VB	
灼热丝易燃指数 (3.0 mm)	960 °C	IEC 60695-2-12
热灯丝点火温度 (3.0 mm)	900 °C	IEC 60695-2-13
电气性能	值	测试方法
热丝引燃 (HWI) (3.0 mm)	PLC 0	UL 746
相比耐漏电起痕指数(CTI)	PLC 4	UL 746
热性能	值	测试方法
RTI Elec		UL 746
1.5 mm	80.0 °C	
3.0 mm	80.0 °C	
RTI Imp		UL 746
1.5 mm	80.0 °C	
3.0 mm	80.0 °C	
RTI		UL 746
1.5 mm	80.0 °C	
3.0 mm	80.0 °C	
物理性能	值	测试方法
室外适用性	f1	UL 746C