



Sicostirolo® CR H 3444

Ravago Manufacturing Europe - High Impact Polystyrene

General Information

Product Description

PS compound, high impact, black

General

Material Status	• Commercial: Active
Availability	• Europe
Recycled Content	• Yes
Features	• High Impact Resistance
Appearance	• Black

Properties ¹

Physical	Nominal Value	Unit	Test Method
Density	1.05	g/cm ³	ISO 1183
Melt Mass-Flow Rate (MFR) (200°C/5.0 kg)	7.0	g/10 min	ISO 1133
Molding Shrinkage - Flow	0.40 to 0.70	%	ASTM D955
Mechanical	Nominal Value	Unit	Test Method
Tensile Stress (Yield)	15.0	MPa	ISO 527-2
Tensile Stress (Break)	12.0	MPa	ISO 527-2
Tensile Strain (Break)	10	%	ISO 527-2
Flexural Modulus	2200	MPa	ISO 178
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact Strength (23°C)	7.0	kJ/m ²	ISO 180
Thermal	Nominal Value	Unit	Test Method
Vicat Softening Temperature	92.0	°C	ISO 306/A50

Notes

¹ Typical properties: these are not to be construed as specifications.