



SINPOLENE MBB005LE

新加坡聚合树脂有限公司 - 低密度聚乙烯

一般信息

产品说明

Sinpolene MBB005LE is a polyethylene-based black masterbatch designed specifically for use in generally-purpose film, blow moulding, injection moulding and extrusion of polyolefins. Sinpolene MBB005LE, has high pigment loading and thus offers high colouring value with good quality and performance. MBB005LE contains extender, which give anti-blocking properties.

CHARACTERISTICS

- Easy processing
- Good dispersion
- Minimal wear effect on processing equipment

总览

材料状态	• 已商用：当前有效	
供货地区	• 非洲和中东	• 亚太地区
添加剂	• 炭黑: 38%	
特性	• 通用	
用途	• 薄膜	
RoHS 合规性	• RoHS 合规	
外观	• 黑色	
形式	• 粒子	
加工方法	• 薄膜挤出 • 吹塑成型	• 挤出 • 注射成型

ASTM & ISO 属性¹

物理性能	额定值	单位制	测试方法
密度 / 比重	1.21		ASTM D792
熔流率 (熔体流动速率) (190°C/10.0 kg)	6.0 到 30	g/10 min	ASTM D1238
含水量	< 0.25		ASTM D3030
炭黑含量	40%		ASTM D1603

补充信息

推荐用量: 2 - 5%

备注

¹ 一般属性：这些不能被视为规格。