



SINPOLENE MBB1402

新加坡聚合树脂有限公司 - 低密度聚乙烯

一般信息

产品说明

SINPOLENE MBB1402 is a modified copolymer based black masterbatch designed specifically for use in injection moulding and extrusion of polyolefins, polystyrene and ABS. SINPOLENE MBB1402 has high pigment loading and thus offers high coloring value with superior quality and performance.

SINPOLENE MBB1402 is delivered as free flowing pellets for processing convenience. It is packed in 25 kg bags. The product should be stored in dry place.

CHARACTERISTICS

- * Easy processing
- * Good dispersion
- * High jetness
- * Minimal wear effect on processing equipment

总览

材料状态	• 已商用：当前有效
供货地区	• 亚太地区
特性	• 可回收材料
用途	• 混料
RoHS 合规性	• RoHS 合规
形式	• 粒子

ASTM & ISO 属性¹

物理性能	额定值	单位制	测试方法
密度 / 比重	1.16		ASTM D792
熔流率 (熔体流动速率) (190°C/21.6 kg)	< 10	g/10 min	ASTM D1238
炭黑含量	> 40	%	ASTM D1603
含水量	< 0.25	%	ASTM D3030

备注

¹ 一般属性：这些不能被视为规格。