



# SINPOLENE MBB1412

新加坡聚合树脂有限公司 - 低密度聚乙烯

## 一般信息

### 产品说明

SINPOLENE MBB1412 is a modified copolymer based black masterbatch designed specifically for use in injection moulding and extrusion of polyolefins, polystyrene and ABS. SINPOLENE MBB1412 has high pigment loading and thus offers high coloring value with superior quality and performance.

SINPOLENE MBB1412 is delivered as free flowing pellets for processing convenience. It is packed in 25 kg bags. The product should be stored in dry place.

### CHARACTERISTICS

- \* Easy processing
- \* Good dispersion
- \* High jetness
- \* Minimal wear effect on processing equipment

### 总览

材料状态	• 已商用：当前有效
供货地区	• 亚太地区
特性	• 可回收材料
用途	• 混料
RoHS 合规性	• RoHS 合规
形式	• 粒子
加工方法	• 化合物挤出

## ASTM & ISO 属性<sup>1</sup>

物理性能	额定值	单位制	测试方法
密度 / 比重	1.16		ASTM D792
熔流率 (熔体流动速率) (190°C/21.6 kg)	> 1.0	g/10 min	ASTM D1238
炭黑含量	40	%	ASTM D1603
含水量	< 0.25	%	ASTM D3030

### 补充信息

Recommended dosage: 1 - 3%

### 备注

<sup>1</sup> 一般属性：这些不能被视为规格。