



SINPOLENE MBB1512

新加坡聚合树脂有限公司 - 低密度聚乙烯

一般信息

产品说明

SINPOLENE MBB1512 is a masterbatch based on a medium jetness carbon black dispersed in polyethylene. It is designed specifically for use in tubular film blowing, blow moulding, extrusion and injection molding of polyolefins. The ingredients used in MBB1512 are approved by most regulations governing the contact of materials with food.

SINPOLENE MBB1512 is delivered as free flowing pellets for processing convenience.

CHARACTERISTICS

- * Easy processing
- * Good dispersion
- * High jetness
- * Good weather and UV light protection
- * Minimal wear effect on processing equipment

总览

材料状态	• 已商用：当前有效
供货地区	• 非洲和中东 • 亚太地区
添加剂	• 碳黑: 35%
特性	• 通用
用途	• 非特定食品应用
RoHS 合规性	• RoHS 合规
外观	• 黑色
形式	• 粒子
加工方法	• 注射成型

ASTM & ISO 属性¹

物理性能	额定值	单位制	测试方法
密度 / 比重	1.14		ASTM D792
熔流率 (熔体流动速率) (190°C/10.0 kg)	10 到 30	g/10 min	ASTM D1238
含水量	< 0.25	%	ASTM D3030
炭黑含量	35	%	ASTM D1603

补充信息

Recommended dosage: 1 - 3%

备注

¹ 一般属性：这些不能被视为规格。