



SINPOLENE MBB3462

新加坡聚合树脂有限公司 - 低密度聚乙烯

一般信息

产品说明

SINPOLENE MBB 3462 is a polyethylene-based black masterbatch designed specifically for use in food contact application film. SINPOLENE MBB3462 has high pigment loading and thus offers high coloring value with superior quality and performance.

SINPOLENE MBB 3462 is delivered as free flowing pellets for processing convenience.

CHARACTERISTICS

- * Easy processing
- * Good dispersion
- * High jetness
- * Minimal wear effect on processing equipment

总览

材料状态	• 已商用：当前有效		
供货地区	• 亚太地区		
用途	• 母料	• 片材	
外观	• 黑色		
形式	• 粒子		
加工方法	• 挤出	• 注射成型	

ASTM & ISO 属性¹

物理性能	额定值	单位制	测试方法
密度 / 比重	1.14		ASTM D792
熔流率 (熔体流动速率) (190°C/10.0 kg)	< 35	g/10 min	ASTM D1238
炭黑含量	40	%	ASTM D1603
含水量	< 0.20	%	ASTM D3030

补充信息

Recommended dosage: 2 - 5%

FOOD CONTACT - Raw materials selected for the formulation are in compliance with FDA regulation.

备注

¹ 一般属性：这些不能被视为规格。