



SINPOLENE MBB7512

新加坡聚合树脂有限公司 - 低密度聚乙烯

一般信息

产品说明

SINPOLENE MBB7512 is a masterbatch based on a furnace carbon black dispersed in polyethylene. It is designed specifically for use in general film, mulch film, extrusion of sheet and injection molding of polyethylene.

SINPOLENE MBB7512 is delivered as free flowing pellets for processing convenience. The product should be stored in dry place.

CHARACTERISTICS

- * Easy processing
- * Good dispersion
- * Higher jetness
- * Good weather and UV light protection
- * Minimal wear effect on processing equipment

总览

材料状态	• 已商用：当前有效		
供货地区	• 亚太地区		
用途	• 薄膜	• 母料	• 片材
RoHS 合规性	• RoHS 合规		
外观	• 黑色		
形式	• 粒子		
加工方法	• 吹塑薄膜	• 片材挤出成型	

ASTM & ISO 属性¹

物理性能	额定值	单位制	测试方法
密度 / 比重	1.16		ASTM D792
熔流率 (熔体流动速率) (190°C/21.6 kg)	25 到 130	g/10 min	ASTM D1238
炭黑含量	40	%	ASTM D1603
含水量	< 0.20	%	ASTM D3030

补充信息

Recommended dosage: 2 - 5%

EU Food Contact 10/2011 compliance

备注

¹ 一般属性：这些不能被视为规格。