



SINPOLENE MBB5821

新加坡聚合树脂有限公司 - 线性低密度聚乙烯

一般信息

产品说明

SINPOLENE MBB5821 is a masterbatch based on a furnace carbon black dispersed in polyethylene. It is designed specifically for use in outdoor geomembrane application and other environments where good weathering resistance is required.

SINPOLENE MBB5821 is delivered as free flowing pellets for processing convenience. The product should be stored in dry place.

CHARACTERISTICS

- * Easy processing
- * Good dispersion
- * Higher jetness
- * Good weathering resistance
- * Minimal wear effect on processing equipment

总览

材料状态	• Preliminary Data
供货地区	• 亚太地区
特性	• 抗氧化性 • 耐紫外光安定化
用途	• 母料 • 土工膜
RoHS 合规性	• RoHS 合规
外观	• 黑色
形式	• 粒子
加工方法	• 吹塑薄膜 • 片材挤出成型

ASTM & ISO 属性¹

物理性能	额定值	单位制	测试方法
熔流率 (熔体流动速率) (190°C/10.0 kg)	< 20	g/10 min	ASTM D1238
炭黑含量	40	%	ASTM D1603
含水量	< 0.20	%	ASTM D3030

补充信息

Customised

备注

¹ 一般属性：这些不能被视为规格。