



SINPOLENE MBB1232

新加坡聚合树脂有限公司 - 聚乙烯

一般信息

产品说明

SINPOLENE MBB 1232 is a highly pigmented and high jetness universal black masterbatch specifically designed for injection moulding and extrusion of polypropylene, polystyrene, ABS and SAN.

SINPOLENE MBB 1232 is delivered as free-flowing pellets for processing convenience. It is packed in 25 kg bags. The product should be stored in dry place.

SINPOLENE MBB 1232 has uniform dispersion and offers high colouring value and UV light protection.

总览

材料状态	• 已商用：当前有效
供货地区	• 亚太地区
特性	• 可回收材料
用途	• 混料 • 母料
机构评级	• UL 94 HB
RoHS 合规性	• RoHS 合规
外观	• 黑色
形式	• 粒子
加工方法	• 复合 • 注射成型

ASTM & ISO 属性¹

物理性能	额定值	单位制	测试方法
密度 / 比重	1.18		ASTM D792
熔流率 (熔体流动速率) (190°C/10.0 kg)	< 15	g/10 min	ASTM D1238
炭黑含量	45	%	ASTM D1603
含水量	< 0.25	%	ASTM D3030

补充信息

Recommended dosage: 1 - 3%

备注

¹ 一般属性：这些不能被视为规格。